



- * Nickel plated brass body
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * M18 x 1.0 body thread form
- * LED status indicator
- * Short circuit and reverse polarity protection
- * Sensitivity adjuster for optimal adaptation to the application
- * Supplied complete with 2 body locknuts
- * All other accessories sold separately
- * Cables required for connection
- * CE, UL, CSA Approvals

Pepperl & Fuchs

Visolux OB M18 Photoelectric Sensors



M12 Plug-In Connection

| Visolux OB Photoelectric Sensors | | | 10 - 30V DC | | NPN |
|----------------------------------|-----------------------|----------------------------|-------------------|-----------------------------|-----------|
| Style | Part Number | Description | Sensing Range (m) | Switch Mode | Output |
| | OBE10M/087791 | Transmitter/Receiver | 10.0 | Light On/Dark On Selectable | 100mA NPN |
| | OBS4000/087799 | Polarised Retro Reflective | 4.0 | | |
| | OBT500/087795 | Diffuse Reflective | 0.5 | | |
| | OBT200/087991 | Diffuse Reflective | 0.2 | | |

| Visolux OB Photoelectric Sensors | | | 10 - 30V DC | | PNP |
|----------------------------------|-----------------------|----------------------------|-------------------|-----------------------------|-----------|
| Style | Part Number | Description | Sensing Range (m) | Switch Mode | Output |
| | OBE10M/087793 | Transmitter/Receiver | 10.0 | Light On/Dark On Selectable | 100mA PNP |
| | OBS4000/087801 | Polarised Retro Reflective | 4.0 | | |
| | OBT500/087797 | Diffuse Reflective | 0.5 | | |
| | OBT200/087993 | Diffuse Reflective | 0.2 | | |

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk