



- * Polycarbonate body with PMMA lens
- * Ingress protection IP67
- * Operating temperature -30°C to +60°C
- * LED status indicator
- * Overload, short circuit & reverse polarity protection
- * Adjustable model features variable background and foreground suppression
- * Accessories sold separately
- * Cables required for connection
- * CE, UL approvals

Pepperl & Fuchs

ML100

Photoelectric Sensors



M8 Plug-In Connection

ML100 Photoelectric Sensors				10 - 30V DC	NPN
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	M+MV100/214744	Transmitter/Receiver	10.0	Light On/Dark On Selectable	100mA NPN
	ML100-55/210535	Polarised Retro Reflective	7.0		
	ML100-8/210539	Diffuse Reflective	1.0		
	ML100-8H/216896	Diffuse Reflective (Adjustable Suppression)	0.05 - 0.35 Adjustable BGS		

ML100 Photoelectric Sensors				10 - 30V DC	PNP
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	M+MV100/221486	Transmitter/Receiver	10.0	Light On/Dark On Selectable	100mA PNP
	ML100-55/210533	Polarised Retro Reflective	7.0		
	ML100-8/210537	Diffuse Reflective	1.0		
	ML100-8H/216895	Diffuse Reflective (Adjustable Suppression)	0.05 - 0.35 Adjustable BGS		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk