



- * Plastic PBT housing
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * LED status indicators
- * Sensitivity adjuster for distance setting
- * Accessories sold separately
- * CE Approval

Pepperl & Fuchs

Standard Visolux RLK39 Photoelectric Sensors



M20 Cable Gland Entry

Standard Visolux RLK39 Photoelectric Sensors			24 - 240V AC / 12 - 240V DC		Relay
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	LA+LK39/088806	Transmitter/ Receiver	20.0	Light On/Dark On Selectable	SP N/O Relay
	RLK39-55/088814	Retro Reflective	20.0		
	RLK39-54/088822	Polarised Retro Reflective	7.0		
	RLK39-8/088827	Diffuse Reflective	2.0		
	RLK39-8/088833	Diffuse Reflective	0.8		

Pepperl & Fuchs

Timer Option Visolux RLK39 Photoelectric Sensors

- * Plastic PBT housing
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * LED status indicators
- * Sensitivity adjuster for distance setting
- * Accessories sold separately
- * CE Approval
- * **Device complete with multifunction timer**



M20 Cable Gland Entry

Timer Option Visolux RLK39 Photoelectric Sensors			24 - 240V AC / 12 - 240V DC		Relay
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	LA+LK39/088807	Transmitter/ Receiver + Timer	20.0	Light On/Dark On Selectable	SP N/O Relay
	RLK39-55/088815	Retro Reflective + Timer	20.0		
	RLK39-54/088823	Polarised Retro Reflective + Timer	7.0		
	RLK39-8/088828	Diffuse Reflective + Timer	2.0		
	RLK39-8/088834	Diffuse Reflective + Timer	0.8		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk