




- * Nickel plated brass body
- * Ingress Protection IP67
- * Operating temperature -25°C to +70°C
- * LED status indicator
- * Short circuit and reverse polarity protection
- * Supplied complete with 2 body locknuts
- * Cables required for plug-in connection
- * CE Approval

Pepperl & Fuchs


NB 4 Wire DC Inductive Proximity Switches



M12 Plug-In Connection

NB Inductive Proximity Switches			10 - 30V DC		NPN
Style	Part Number	Sensing Distance (mm)	Installation Mode	Body Size (mm)	
				Thread	Length
 <p>Antivalent (N/O or N/C)</p>	NBB1.5-8GM50A0V	1.5	Flush	M8 x 1.0	50
	NBB2-12GM60A0V1	2.0		M12 x 1.0	
	NBB5-18GM60A0V1	5.0		M18 x 1.0	
	NBB8-18GM60A0V1	8.0		M18 x 1.0	
	NBB10-30GM60A0V	10.0		M30 x 1.5	
	NBN4-12GM60A0V1	4.0	Non-Flush	M12 x 1.0	60
	NBN8-18GM60A0V1	8.0		M18 x 1.0	
	NBN15-30GM60A0V	15.0		M30 x 1.5	

2m Pre-Cabled Connection

NB Inductive Proximity Switches			10 - 30V DC		NPN
Style	Part Number	Sensing Distance (mm)	Installation Mode	Body Size (mm)	
				Thread	Length
 <p>Antivalent (N/O or N/C)</p>	NBB1.5-8GM60-A0	1.5	Flush	M8 x 1.0	60
	NBB2-12GM60-A0	2.0		M12 x 1.0	
	NBB5-18GM60-A0	5.0		M18 x 1.0	
	NBB8-18GM60-A0	8.0		M18 x 1.0	
	NBB10-30GM60-A0	10.0		M30 x 1.5	
	NBN2-8GM60-A0	2.0	Non-Flush	M8 x 1.0	60
	NBN4-12GM60-A0	4.0		M12 x 1.0	
	NBN8-18GM60-A0	8.0		M18 x 1.0	
	NBN15-30GM60-A0	15.0		M30 x 1.5	

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk