



- * Die-Cast Aluminium Construction
- * 6A switch rating
- * Ingress Protection IP65
- * Operating temperature -25°C to +80°C
- * Integral floor fixing points
- * Large wiring compartment
- * CE, UL, CSA, TUV Approvals

.steute

**GF
Foot Switches**



M20 Conduit Entry

GF Foot Switches					
Style	Part Number	Description	Operation	Contacts	
				Configuration	Action
	GF-10/1S	Open Single Pedal	Momentary	1 N/O + 1 N/C	Slow Action
	GF-20/2S			2 N/O + 2 N/C	
	GF-10/1S-RE		Latched	1 N/O + 1 N/C	
	GFS-10/1S	Covered Single Pedal	Momentary	1 N/O + 1 N/C	
	GFS-20/2S			2 N/O + 2 N/C	
	GFS-10/1S-RE		Latched	1 N/O + 1 N/C	
	GF52-10S/10S	Covered Double Pedal	Momentary	1 N/O + 1 N/C	

- * Die-cast aluminium construction
- * Switch rating determined by 789 Wireless Receiver
- * Ingress Protection IP67
- * Operating temperature 0°C to +65°C
- * Signal range is 30m indoor, 300m outdoor
- * Output signal high on actuation
- * High visibility RAL 2004 paint finish
- * No power supply needed
- * CE, En-Ocean Approvals

.steute

**EF95
Wireless Foot Switches**



Wireless Connection

EF95 Wireless Foot Switches					
Style	Part Number	Description	Connectivity	Contacts	
				Configuration	Data Rate
	GFIF	Open Single Pedal	Wireless En-Ocean	1 N/O	6000 Packets/Hour
	GFSIF	Covered Single Pedal			

N.B. Wireless switches require 789 Wireless Receivers

Leeds
Tel: 0113 243 0203

Sheffield
Tel: 0114 243 1841

Gateshead
Tel: 0191 460 2233

Manchester
Tel: 0161 876 4337

Glasgow
Tel: 0141 892 0166

Walsall
Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk