



- \* Thermoplastic enclosure
- \* 4 x Relay outputs @ 16A
- \* 4 x Change over @ 8A
- \* Ingress Protection IP20 (Receiver)
- \* Operating temperature 0°C to +55°C
- \* Transmitter/receiver assignment by teaching mode
- \* LED status indicators
- \* 4 channel 868MHz frequency band
- \* SMA plug-in connector for external antenna
- \* CE, En-Ocean Approvals

# .steute

789

## Wireless Receivers



DIN Rail Mounting

789 Wireless Receivers					
24V DC					
Style	Part Number	Switching Frequency	Number of Channels	Inputs	Outputs
	01080255/789601	9000 Packets/Hour	4	4 x Wireless Transmitters	4 x N/O Relay
	01080256/789602	9000 Packets/Hour	4	4 x Wireless Transmitters	4 x Change-Over
	0108254	Antenna	N/A	Plug-In	N/A

- \* Thermoplastic Enclosure
- \* Switch rating determined by 789 Wireless Receiver
- \* Ingress Protection IP67
- \* Operating temperature 0°C to +65°C
- \* Signal range is 30m indoor, 300m outdoor
- \* Output signal high on actuation
- \* Slotted mounting holes
- \* No power supply needed
- \* CE, En-Ocean Approvals

# .steute

EF95

## Wireless Position Switches



Wireless Connection

EF95 Wireless Position Switches					
Self Powered					
Style	Part Number	Description	Connectivity	Contacts	
				Configuration	Data Rate
	EF95W	Top Pin Plunger	Wireless En-Ocean	1 N/O	6000 Packets/Hour
	EF95WK	Push Button Plunger			
	EF95R	Top Roller Plunger			
	EF95D	Side Roller lever			
	EF95DS	Adjustable Roller Lever			
	EF95WH	Top Roller Lever			
	EF95TK	Coil Spring Rod			

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403 426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)