



- * Chrome plated brass body
- * Ingress Protection IP68
- * Operating temperature -25°C to +70°C
- * LED status indicator
- * Reverse polarity and wire break protection
- * Supplied complete with 2 body locknuts
- * All other accessories sold separately
- * H1141 plug-in connection
- * EMC immunity to EN61000-4.6
- * Cables required for connection
- * CE Approvals


Turck

UPROX

Inductive Proximity Switches



M12 Plug-In Connection (H1141)

UPROX Inductive Proximity Switches			10 - 30V DC		PNP
Style	Part Number	Sensing Range (mm)	Installation Mode	Body Size (mm)	
				Thread	Length
 <p>Normally Open (N/O)</p>	BI3U-M12AP6X-H	3.0	Flush	M12 x 1.0	50
	BI5U-M18AP6X-H	5.0		M18 x 1.0	50
	BI10U-M30AP6X-H	10.0		M30 x 1.5	60
	NI8U-M12AP6X-H	8.0	Non-Flush	M12 x 1.0	50
	NI12U-M18AP6X-H	12.0		M18 x 1.0	50
	NI20U-M30AP6X-H	20.0		M30 x 1.5	60

- * Chrome plated brass body
- * Ingress Protection IP68
- * Operating temperature -25°C to +70°C
- * LED status indicator
- * Reverse polarity and wire break protection
- * Supplied complete with 2 body locknuts
- * All other accessories sold separately
- * EMC immunity to EN61000-4.6
- * CE Approvals


Turck

UPROX

Inductive Proximity Switches



2m Pre-Cabled Connection

UPROX Inductive Proximity Switches			10 - 30V DC		PNP
Style	Part Number	Sensing Range (mm)	Installation Mode	Body Size (mm)	
				Thread	Length
 <p>Normally Open (N/O)</p>	BI1.5U-EG08AP6X	1.5	Flush	M8 x 1.0	50
	BI3U-M12AP6X	3.0		M12 x 1.0	50
	BI5U-M18AP6X	5.0		M18 x 1.0	50
	BI10U-M30AP6X	10.0		M30 x 1.5	60
	NI4U-EG08AP6X	4.0	Non-Flush	M8 x 1.0	50
	NI8U-M12AP6X	8.0		M12 x 1.0	50
	NI12U-M18AP6X	12.0		M18 x 1.0	50
	NI20U-M30AP6X	20.0		M30 x 1.5	60

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk