



22.5mm Panel Mount Indicators

Certification Information

- * Certification Number BAS01ATEX1062X
- * Approved to II 1G EEx ia IIC T4
- * Ingress Protection IP66 (Front)
- * Ambient Temperature Range -40°C up to +60°C

Features

- * Polycarbonate lens with Nylon 6 body
- * Typical lamp life of 100,000 hours
- * 20mA constant current
- * Standard 22.5mm cut-out for panel mounting
- * Simple connection via suitable galvanic isolator
- * Suitable galvanic isolators include KFD0-SD2EX11045 or equivalent



LED Cluster 22.5mm Panel Mounted Indicators



Part Number	Description	Colour	Voltage
BA390AMBER	LED Cluster Indicator		24V DC
BA390BLUE			
BA390GREEN			
BA390RED			
BA390WHITE			

Accessories



Part Number	Description
BA390LEGEND	Legend plate

- Zone 0 ✓
- Zone 1 ✓
- Zone 2 ✓
- Zone 20 X
- Zone 21 X
- Zone 22 X
- IEC Ex ✓



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk