



**Certification Information**

- \* Certification Number SIRA03ATEX3206
- \* Approved to II 2GD Ex em IIC T4
- \* Ingress Protection IP66 and IP67
- \* Ambient Temperature Range -45°C to +55°C (18/36W Versions)
- \* Ambient Temperature Range -45°C to +50°C (58W Version)

**Features**

- \* Polycarbonate body and lamp envelope
- \* Painted stainless steel external reflector
- \* Electronic high frequency control gear with end of life lamp shut down
- \* For use with G13 cap T8 bi-pin lamps
- \* Terminals for up to 4mm<sup>2</sup> cables, loop in-loop out
- \* 2 x 20mm entries, internally earthed



# Victor

## Trident VL125 Fluorescent Luminaires

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



**Trident VL125 Fluorescent Luminaires**

Part Number	Voltage	Configuration	Dimensions (mm)			Weight (kg)
			Length	Width	Fixing Centres	
TRIE/218/BI	110 - 254V AC	2 x 18W	995	181	400	3.8
TRIE/236/BI		2 x 36W	1605		700	5.4
TRIE/258/BI		2 x 58W	1905		700	6.2

**Certification Information**

- \* Certification Number SIRA03ATEX3206
- \* Approved to II 2GD Ex em IIC T4
- \* Ingress Protection IP66 and IP67
- \* Ambient Temperature Range -15°C to +55°C (18/36W Versions)
- \* Ambient Temperature Range -15°C to +50°C (58W Version)

**Features**

- \* Polycarbonate body and lamp envelope
- \* Painted stainless steel external reflector
- \* Electronic high frequency control gear with end of life lamp shut down
- \* For use with G13 cap T8 bi-pin lamps
- \* Emergency pack utilises a dedicated 11W Compact PL light
- \* 3 hour emergency duration at 25°C
- \* Terminals for up to 4mm<sup>2</sup> cables, loop in-loop out
- \* 2 x 20mm entries, internally earthed



# Victor

## Trident VL126 Emergency Fluorescent Luminaires

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



**Trident VL126 Emergency Fluorescent Luminaires**

Part Number	Voltage	Configuration	Dimensions (mm)			Weight (kg)
			Length	Width	Fixing Centres	
TRIE/218/BI/EM	220 - 254V AC	2 x 18W	995	181	400	5.4
TRIE/236/BI/EM		2 x 36W	1605		700	7.0
TRIE/258/BI/EM		2 x 58W	1905		700	7.8

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)