



Raytec

Spartan LED Linear



Certification Information

- * Certification Number CML14ATEX3119
- * Approved to II 2G Ex emb IIC T4 Gb
- * Approved to II 2D Ex tb IIIC T76°C Db
- * Ingress Protection IP66/67
- * Ambient Temperature Range -20°C to +55°C

Features

- * Marine grade aluminium enclosure with epoxy powder coat finish
- * Tough polycarbonate diffuser
- * Field replaceable power supply module and LED array
- * Interchangeable power supplies and LED array between the SPX-WL84 and SPX-WL168
- * Platinum SMT LED's, CRI 70+, 6000K+
- * Terminals for 0.5 to 4mm² cables, through wired
- * 2 x M20 cable entries each end with large termination area
- * Low voltage version also available, 18-30V AC/DC

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



Spartan WL Linear LED Light

Part Number	Voltage	Lumen Output	Power Consumption (W)	Dimensions (mm) (l x w x d)	Weight (Kg)
SPX-WL84	110 - 254V 50/60Hz	2,500	34	772 x 174 x 108	6
SPX-WL168		5,000	68	1292 x 174 x 108	9

Spartan Linear Accessories

Part Number	Description
SPX-BKT-CM	316L Stainless Steel Ceiling Mount Bracket -Pair

Raytec

Spartan LED Emergency Linear



Certification Information

- * Certification Number CML14ATEX3119
- * Approved to II 2G Ex emb IIC T4 Gb
- * Approved to II 2D Ex tb IIIC T76°C Db
- * Ingress Protection IP66/67
- * Ambient Temperature Range -20°C to +55°C

Features

- * Marine grade aluminium enclosure with epoxy powder coat finish
- * Tough polycarbonate diffuser
- * Field replaceable power supply module, battery and LED array
- * Interchangeable power supplies, LED array and batteries between the SPX-WL84-EM25 and SPX-WL168-EM25
- * Upto 3 hours emergency output at 25% power
- * Alternative factory set emergency output options are available
- * Platinum SMT LED's, CRI 70+, 6000K+
- * Terminals for 0.5 to 4mm² cables, through wired
- * 2 x M20 cable entries each end with large termination area

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



Spartan WL Emergency Linear LED Light

Part Number	Voltage	Lumen Output	Power Consumption (W)	Dimensions (mm) (l x w x d)	Weight (Kg)
SPX-WL84-EM25	110 - 254V 50/60Hz	2,500	37	772 x 174 x 108	7
SPX-WL168-EM25		5,000	71	1407 x 174 x 108	10

Spartan Linear Accessories

Part Number	Description
SPX-BKT-CM	316L Stainless Steel Ceiling Mount Bracket -Pair

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 242 8840

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk