

# Data sheet

Order No.: 1792278

Type: MVSTBR 2,5/ 5-ST-5,08

Plug component, Screw connection with tension sleeve



The figure shows a 10-position version of the product

## 1 Main features



• No. of pos.	5	• Nominal current	12 A
• Conductor cross section	2.5 mm <sup>2</sup>	• Nominal voltage	320 V
• Color	green	• Connection direction	90 °
• Pitch	5.08 mm	• Type of packaging	packed in cardboard
• Connection method	Screw connection with tension sleeve		

## 2 Your advantages

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Allows connection of two conductors



Make sure you always use the latest documentation.


It can be downloaded at: [phoenixcontact.net/product/1792278](http://phoenixcontact.net/product/1792278)

**1792278 MVSTBR 2,5/ 5-ST-5,08****3 Table of contents**

1	Main features.....	1
2	Your advantages .....	1
3	Table of contents .....	2
4	3D model in PDF can be activated (Acrobat Reader only).....	3
5	item properties.....	4
	5.1 Connection capacity .....	4
	5.2 Material data .....	4
6	Dimensions.....	4
	6.1 Dimensions for the product .....	5
7	Series drawing.....	6
8	Packaging information .....	7
9	Application.....	7
	9.1 Temperature limit values .....	7
10	Mechanical tests.....	8
	10.1 Termination and connection method.....	8
	10.2 Pull-out test .....	8
11	Electrical tests .....	9
	11.1 Electrical data .....	9
	11.2 Air and creepage distances .....	9
12	Current carrying capacity/derating curves .....	10
13	Environmental and durability tests .....	12
	13.1 Vibration test .....	12
14	Classification for connectors.....	12
15	Approvals .....	12
16	Commercial Data.....	14
17	corresponding headers.....	14
18	Accessories.....	14
19	Combination tests.....	16

1792278 MVSTBR 2,5/ 5-ST-5,08

**4 3D model in PDF can be activated (Acrobat Reader only)**



**1792278 MVSTBR 2,5/ 5-ST-5,08****5 item properties**

Order No.	1792278
Type	MVSTBR 2,5/ 5-ST-5,08
Type of contact	Female connector
Range of articles	MVSTBR 2,5/...-ST
Pitch	5.08 mm
Number of positions	5
Connection method	Screw connection with tension sleeve
Drive form screw head	Slotted
Screw thread	M3
Tightening torque	0.5 Nm ... 0.6 Nm
Note on tightening torque	
Locking	without

**5.1 Connection capacity**

Conductor cross section, solid	0.2 mm <sup>2</sup> to 2.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> to 2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil	24 to 12
2 conductors with same cross section, solid	0.2 mm <sup>2</sup> to 1 mm <sup>2</sup>
2 conductors with same cross section, stranded	0.2 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Conductor cross section flexible, with ferrule without plastic sleeve	0.25 mm <sup>2</sup> to 2.5 mm <sup>2</sup>
Conductor cross section flexible, with ferrule with plastic sleeve	0.25 mm <sup>2</sup> to 2.5 mm <sup>2</sup>
2 conductors with same cross section, stranded, with ferrule without plastic sleeve	0.25 mm <sup>2</sup> to 1 mm <sup>2</sup>
2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve	0.5 mm <sup>2</sup> to 1.5 mm <sup>2</sup>
Cylindrical gauge a x b / diameter	2.8 mm x 2.0 mm / 2.4 mm
Stripping length	7 mm

**5.2 Material data**

<b>Material of metal parts</b>	
Note	WEEE/RoHS-compliant, whisker-free acc. to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Terminal point surface	Sn 5 µm ... 7 µm
Surface contact area	Sn 5 µm ... 7 µm
Surface characteristics	hot-dip tin-plated
<b>Insulating material data</b>	
Insulating material	PA
CTI according to IEC 60112	600
Flammability rating according to UL 94	V0
Color	green (6021)
Glow wire flammability index GWFI according to EN 60695-2-12	850
Glow wire ignition temperature GWIT according to EN 60695-2-13	775
Temperature for the ball pressure test according to EN 60695-10-2	125 °C

**6 Dimensions**

**1792278 MVSTBR 2,5/ 5-ST-5,08**


---

**6.1 Dimensions for the product**

Length	12.5 mm
Width	25.4 mm
Total height	26 mm
Dimension a	20.32 mm

1792278 MVSTBR 2,5/ 5-ST-5,08

7 Series drawing



**1792278 MVSTBR 2,5/ 5-ST-5,08****8 Packaging information**

Type of packaging	packed in cardboard
Pieces per package	100

**9 Application****9.1 Temperature limit values**

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C (dependent on the derating curve)

**1792278 MVSTBR 2,5/ 5-ST-5,08****10 Mechanical tests**

Mechanical test group A	
Specification	IEC 61984:2008-10
Visual test	Test passed
Specification	IEC 60512-1-1:2002-02
Dimensional test	Test passed
Specification	IEC 60512-1-2:2002-02
Resistance of marking	Test passed
Specification	IEC 60068-2-70:1995-12
Insertion and withdrawal force	Test passed
Specification	IEC 60512-13-2:2006-02
No. of cycles	25
Insertion strength per pos. approx.	8 N
Withdraw strength per pos. approx.	6 N
Polarization and coding	Test passed
Specification	IEC 60512-13-5:2006-02
Test force	20 N
Contact retention in insert	Test passed
Specification	IEC 60512-15-1:2008-05
Test force per pos.	33 N

**10.1 Termination and connection method**

Specification	IEC 60999-1:1999-11
Check for damage to conductor or loosening	Test passed

**10.2 Pull-out test**

Termination and connection method: pull-out test	
Specification	IEC 60999-1:1999-11
Result	Test passed
Conductor cross section/conductor type/tractive force actual value	0.2 mm <sup>2</sup> / solid / > 10 N
Conductor cross section/conductor type/tractive force actual value	0.2 mm <sup>2</sup> / stranded / > 10 N
Conductor cross section/conductor type/tractive force actual value	2.5 mm <sup>2</sup> / solid / > 50 N
Conductor cross section/conductor type/tractive force actual value	2.5 mm <sup>2</sup> / stranded / > 50 N

**1792278 MVSTBR 2,5/ 5-ST-5,08****11 Electrical tests****11.1 Electrical data**

Rated current / conductor cross section	12 A / 2.5 mm <sup>2</sup>
Rated insulation voltage (III/2)	320 V
Rated surge voltage (III/2)	4 kV
Contact resistance	2.5 mΩ
Degree of pollution	2

**11.2 Air and creepage distances**


Component	Plug component		
Specification	IEC 60664-1:2007-04		
Mains type	unearthed mains		
Insulating material group	I		
Comparative tracking index (IEC 60112:2003-01)	CTI 600		
Rated insulation voltage	250 V	320 V	630 V
Rated surge voltage	4 kV	4 kV	4 kV
Degree of pollution	3	2	2
Overvoltage category	III	III	II
Minimum clearance case A (inhomogeneous field)	3 mm	3 mm	3 mm
Minimum value of the creepage path requirement in acc. with table	4 mm	1.6 mm	3.2 mm
Note on connection cross section	With connected conductor 4 mm <sup>2</sup> (solid).		

1792278 MVSTBR 2,5/ 5-ST-5,08


12 Current carrying capacity/derating curves

Specification	IEC 61984:2008-10
Note	Representation based on IEC 60512-5-2:2002-02
Reduction factor	0.8
Number of positions	See diagram
Conductor cross section	2.5 mm <sup>2</sup>


Type: MVSTBR 2,5/...-ST-5,08 with CC 2,5/...-G-5,08 P26THR



Type: MVSTBR 2,5/...-ST-5,08 with CCV 2,5/...-G-5,08 P26THR




Type: MVSTB(R/W) 2,5/...-ST-5,08 with MDSTBA 2,5/...-G-5,08




**1792278 MVSTBR 2,5/ 5-ST-5,08**


Type: MVSTB(R/W) 2,5/...-ST with MDSTBV 2,5/...-G-5,08



Type: MVSTBR 2,5/...-ST-5,08 with MSTBVK 2,5/...-G-5,08



Type: MVSTB(R/W) 2,5/...-ST-5,08 with MDSTBW 2,5/...-G-5,08



Type: MVSTB(R/W) 2,5/...-ST with MDSTBVA 2,5/...-G-5,08

84916\_1000\_en

Type: MVSTBR 2,5/...-ST-5,08 with MSTBA 2,5/...-G-5,08

88567\_1000\_en


**1792278 MVSTBR 2,5/ 5-ST-5,08****13 Environmental and durability tests****13.1 Vibration test**


Specification	IEC 60068-2-6:2007-12
Result	Test passed
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm (10 - 60.1 Hz)
Acceleration	5 g (60.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis


**14 Classification for connectors**


Specification	IEC 61984:2008-10
Main features	Connectors without switching capacity (COC)
Construction form	Fixed connectors
Strain relief elements	without strain relief
Connection method	Can be reconnected
Protection against electric shock	Not encapsulated - touch-proof when inserted
Protective conductor	without PE
Lock	no
Connection method	Screw terminal points

**15 Approvals**

CSA 				
Use group	B	D		
mm <sup>2</sup> /AWG/kcmil	28-12	28-12		
Voltage	300 V	300 V		
Current	10 A	10 A		

VDE Gutachten mit Fertigungsüberwachung 				
mm <sup>2</sup> /AWG/kcmil	0.2-2.5			
Voltage	250 V			
Current	12 A			

IECEE CB Scheme 				
mm <sup>2</sup> /AWG/kcmil	0.2-2.5			
Voltage	250 V			
Current	12 A			

cULus Recognized 				
Use group	B	D		
mm <sup>2</sup> /AWG/kcmil	30-12	30-12		
Voltage	300 V	300 V		
Current	15 A	10 A		

2017-10-23

Product version 03

Document revision 0

**1792278 MVSTBR 2,5/ 5-ST-5,08**

EAC ENEC

**1792278 MVSTBR 2,5/ 5-ST-5,08****16 Commercial Data**

Order No.	1792278
Type	MVSTBR 2,5/ 5-ST-5,08
Pieces per package	100
Net weight	10.6 g
GTIN	4017918044756
	Information that applies locally, see link on page 1
Country of origin	Information that applies locally, see link on page 1

**17 corresponding headers**

Order No.	Type
1735853	MSTBW 2,5/ 5-G-5,08
1755765	MSTBVA 2,5/ 5-G-5,08
1757271	MSTBA 2,5/ 5-G-5,08
1758047	MSTBV 2,5/ 5-G-5,08
1759046	MSTB 2,5/ 5-G-5,08
1762004	MDSTBV 2,5/ 5-G-5,08
1767407	SMSTBA 2,5/ 5-G-5,08
1769492	SMSTB 2,5/ 5-G-5,08
1770973	MSTBA 2,5/ 5-G-5,08-LA
1840010	MDSTBW 2,5/ 5-G-5,08
1842092	MDSTBA 2,5/ 5-G-5,08
1842542	MDSTB 2,5/ 5-G-5,08
1845361	MDSTBVA 2,5/ 5-G-5,08
1847136	MSTBO 2,5/ 5-GR-5,08
1850466	MSTBO 2,5/ 5-GL-5,08
1859548	EMSTBVA 2,5/ 5-G-5,08
1880339	EMSTBA 2,5/ 5-G-5,08
1898868	DFK-MSTBA 2,5/ 5-G-5,08
1899168	DFK-MSTBVA 2,5/ 5-G-5,08
1902770	MSTBA 2,5/ 5-G-5,08 THT
1902848	MSTBVA 2,5/ 5-G-5,08 THT
1937266	MSTBA 2,5/ 5-G-5,08 THT-R56
1940444	MSTBVA 2,5/ 5-G-5,08 THT-R56
1954414	CC 2,5/ 5-G-5,08 P26THR
1954618	CC 2,5/ 5-G-5,08 P26THRR56
1954948	CCA 2,5/ 5-G-5,08 P26THR
1955060	CCA 2,5/ 5-G-5,08 P26THRR56
1955413	CCV 2,5/ 5-G-5,08 P26THR
1955552	CCV 2,5/ 5-G-5,08 P26THRR56
1955882	CCVA 2,5/ 5-G-5,08 P26THR
1955992	CCVA 2,5/ 5-G-5,08 P26THRR56

**18 Accessories**

**1792278 MVSTBR 2,5/ 5-ST-5,08**

Description	Order No.	Type
	0805412	SK 5,08/3,8:UNBEDRUCKT
	0805085	SK 5,08/3,8:SO
Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm	1051993	B-STIFT
Actuation tool, for ST terminal blocks, insulated, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip	1205053	SZS 0,6X3,5
Coding profile, is inserted into the slot on the plug or inverted header, red insulating material	1734634	CP-MSTB

1792278 MVSTBR 2,5/ 5-ST-5,08

19 Combination tests




MVSTBR 2,5/...-ST	CC 2,5/...-G	CCA 2,5/...-G	CCV 2,5/...-G	CCVA 2,5/...-G
Specification	IEC 61984	IEC 61984	IEC 61984	IEC 61984
<b>Mechanical tests (A)</b>				
Insertion/withdrawal force per position	approx. 8 N / 6 N		approx. 8 N / 6 N	
Polarization when inserted Requirement >20 N	Test passed		Test passed	
Contact holder in insert Requirements >20 N	Test passed		Test passed	
<b>Durability tests (B)</b>				
Contact resistance R <sub>1</sub>	2.5 mΩ		2.4 mΩ	
Insertion/withdrawal cycles	25		25	
Contact resistance R <sub>2</sub>	2.5 mΩ		2.4 mΩ	
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	4.8 kV		4.8 kV	
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	2.21 kV		2.21 kV	
Insulation resistance Requirements > 5 MΩ	> 0.2 TΩ		> 0.1 TΩ	
<b>Thermal tests (C)</b>				
Tested number of positions	12		12	
Tested conductor cross section	2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>	
Test current	12 A		12 A	
Upper limiting temperature Requirements < 100°C	Test passed		Test passed	
<b>Climatic tests (D)</b>				
Test sequence 1: low temperature storage	-40 °C/2 h		-40 °C/2 h	
Test sequence 2: heat storage	100 °C/168 h		100 °C/168 h	
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle		0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle	
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	4.8 kV		4.8 kV	
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	2.21 kV		2.21 kV	
<b>Environmental and endurance tests (E)</b>				
Specification	IEC 61984:2008-10		IEC 61984:2008-10	
Degree of protection	Finger safety with IP20 test finger		Finger safety with IP20 test finger	

**1792278 MVSTBR 2,5/ 5-ST-5,08**



**MVSTBR 2,5/..-ST**



**MDSTBA 2,5/..-G**



**MDSTBV 2,5/..-G**





**DFK-MSTBA 2,5/..-G**



**MSTBVK 2,5/..-G**

Specification	IEC 61984	IEC 61984	IEC 61984	IEC 61984
<b>Mechanical tests (A)</b>				
Insertion/withdrawal force per position	approx. 8 N / 6 N	approx. 8 N / 6 N		approx. 8 N / 7 N
Polarization when inserted Requirement >20 N	Test passed	Test passed		Test passed
Contact holder in insert Requirements >20 N	Test passed	Test passed		Test is not applicable
<b>Durability tests (B)</b>				
Contact resistance R <sub>1</sub>	2.7 mΩ	3.8 mΩ		3 mΩ
Insertion/withdrawal cycles	25	25		25
Contact resistance R <sub>2</sub>	2.8 mΩ	3.7 mΩ		3.1 mΩ
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	4.8 kV	4.8 kV		4.8 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	2.21 kV	2.21 kV		2.21 kV
Insulation resistance Requirements > 5 MΩ	> 65 GΩ	> 1 GΩ		3 TΩ
<b>Thermal tests (C)</b>				
Tested number of positions	12	12		24
Tested conductor cross section	2.5 mm <sup>2</sup>	2.5 mm <sup>2</sup>		2.5 mm <sup>2</sup>
Test current	10 A	10 A		12 A DC
Upper limiting temperature Requirements < 100°C	Test passed	Test passed		Test passed
<b>Climatic tests (D)</b>				
Test sequence 1: low temperature storage	-40 °C/2 h	-40 °C/2 h		-40 °C/2 h
Test sequence 2: heat storage	100 °C/168 h	100 °C/168 h		100 °C/168 h
Test sequence 3: noxious gas storage (ISO 6988)	0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle	0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle		0.2 dm <sup>3</sup> SO <sub>2</sub> on 300 dm <sup>3</sup> / 40 °C/1 cycle
Rated impulse voltage at sea level Voltage waveform ≥ (1.2/50 μs)	4.8 kV	4.8 kV		4.8 kV
Power-frequency withstand voltage Voltage waveform ≥ (50/60 Hz)	2.21 kV	2.21 kV		2.21 kV
<b>Environmental and endurance tests (E)</b>				
Specification	IEC 61984:2008-10	IEC 61984:2008-10		IEC 61984:2008-10
Degree of protection	Finger safety with IP20 test finger	Finger safety with IP20 test finger		Finger safety with IP20 test finger

**1792278 MVSTBR 2,5/ 5-ST-5,08**



**MVSTBR 2,5/..-ST**

**MDSTBW 2,5/..-G**

**MDSTBVA 2,5/..-G**

**MSTBA 2,5/..-G**

Specification

IEC 61984

IEC 61984

IEC 61984

**Mechanical tests (A)**

Insertion/withdrawal force per position

approx. 8 N / 6 N

approx. 8 N / 6 N

approx. 8 N / 6 N

Polarization when inserted  
Requirement >20 N

Test passed

Test passed

Test passed

Contact holder in insert  
Requirements >20 N

Test passed

Test passed

Test passed

**Durability tests (B)**

Contact resistance R<sub>1</sub>

2.8 mΩ

3.7 mΩ

2.4 mΩ

Insertion/withdrawal cycles

25

25

25

Contact resistance R<sub>2</sub>

2.8 mΩ

3.7 mΩ

2.4 mΩ

Rated impulse voltage at sea level  
Voltage waveform ≥ (1.2/50 μs)

4.8 kV

4.8 kV

4.8 kV

Power-frequency withstand voltage  
Voltage waveform ≥ (50/60 Hz)

2.21 kV

2.21 kV

2.21 kV

Insulation resistance  
Requirements > 5 MΩ

> 0.2 TΩ

> 0.1 TΩ

> 75 TΩ

**Thermal tests (C)**

Tested number of positions

12

12

24

Tested conductor cross section

2.5 mm<sup>2</sup>

2.5 mm<sup>2</sup>

2.5 mm<sup>2</sup>

Test current

10 A

10 A

12 A DC

Upper limiting temperature  
Requirements < 100°C

Test passed

Test passed

Test passed

**Climatic tests (D)**

Test sequence 1: low temperature storage

-40 °C/2 h

-40 °C/2 h

-40 °C/2 h

Test sequence 2: heat storage

100 °C/168 h

100 °C/168 h

100 °C/168 h

Test sequence 3: noxious gas storage  
(ISO 6988)

0.2 dm<sup>3</sup> SO<sub>2</sub> on 300 dm<sup>3</sup>/  
40 °C/1 cycle

0.2 dm<sup>3</sup> SO<sub>2</sub> on 300 dm<sup>3</sup>/  
40 °C/1 cycle

0.2 dm<sup>3</sup> SO<sub>2</sub> on 300 dm<sup>3</sup>/  
40 °C/1 cycle

Rated impulse voltage at sea level  
Voltage waveform ≥ (1.2/50 μs)

4.8 kV

4.8 kV

4.8 kV

Power-frequency withstand voltage  
Voltage waveform ≥ (50/60 Hz)

2.21 kV

2.21 kV

2.21 kV

**Environmental and endurance tests (E)**

Specification

IEC 61984:2008-10

IEC 61984:2008-10

IEC 61984:2008-10

Degree of protection

Finger safety with IP20  
test finger

Finger safety with IP20  
test finger

Finger safety with IP20  
test finger



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)