

**DNV·GL**Certificate No:  
**TAA00000K4****TYPE APPROVAL CERTIFICATE****This is to certify:****That the Electromechanical Relays**with type designation(s)  
**PSR-SCP/SPP-24DC/ESP4/2X1/1X2**

Issued to

**Phoenix Contact GmbH & Co. KG  
Blomberg, Germany**is found to comply with  
**DNV GL rules for classification – Ships****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**

<b>Temperature</b>	<b>D</b>
<b>Humidity</b>	<b>B</b>
<b>Vibration</b>	<b>A</b>
<b>EMC</b>	<b>B</b>
<b>Enclosure</b>	<b>Required protection according to the Rules shall be provided upon installation on board</b>

This Certificate is valid until **2021-07-13**.Issued at **Hamburg** on **2016-07-14**DNV GL local station: **Magdeburg**Approval Engineer: **Heinz Scheffler**for **DNV GL**

Digitally Signed By: Le, Nam

Location: DNVGL Hamburg, Germany

Signing Date: 2016-08-26

.....

**Duy Nam Le**  
**Head of Section**

.....

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id: **262.1-023207-1**  
Certificate No: **TAA00000K4**

## Product description

### Safety relay for emergency stop and safety door monitoring

#### Type:

- SCP: with screw connection
- SPP: with spring-cage connection

#### Data:

- Nominal input voltage UN: 24 V DC
- Contact type: 2 enable current paths, 1 signaling current path
- Maximum switching voltage: 250 V AC/DC
- Minimum switching voltage: 10 V AC/DC
- Limiting continuous current (N/O contact, N/C contact): 6 A
- Maximum inrush current (N/O contact, N/C contact): 6 A
- Minimum switching current: 10 mA
- Maximum shutdown power:
  - 24 V DC; Ohmic load T = 0 ms, 144 W; Inductive load T = 40 ms, 42 W
  - 48 V DC; Ohmic load T = 0 ms, 200 W; Inductive load T = 40 ms, 40 W
  - 110 V DC; Ohmic load T = 0 ms, 77 W; Inductive load T = 40 ms, 35 W
  - 220 V DC; Ohmic load T = 0 ms, 70 W; Inductive load T = 40 ms, 33 W
  - 250 V AC; Ohmic load T = 0 ms, 1500 VA;
- Minimum switching power: 0.2 W

## Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

## Type Approval documentation

Test report :E082797E1, E082797E2, U082797E1, PBS 82797E1, PBS 82797E1, EMC\_21148794, UL-File E140324; SIL3 Certificate from TÜV Rheinland Group, No.:968/EZ 406.01/10

Documents: Data Sheet 100516\_en\_05

## Tests carried out

Applicable tests according to class guideline DNVGL-CG-0339, November 2015.

## Marking of product

The products to be marked with:

- model name
- manufacturer name
- serial number

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

Job Id: **262.1-023207-1**  
Certificate No: **TAA00000K4**

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications  
Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed at least every second year and at renewal of this certificate.  
END OF CERTIFICATE



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)