

KombiSIGN 71 / Flash Beacon 643

**Flashing light element 230VAC BU**

|           |              |
|-----------|--------------|
| Part No.: | 643.500.68   |
| Series:   | KombiSIGN 71 |

**MECHANICAL DATA**

|                             |                           |
|-----------------------------|---------------------------|
| Height                      | 66 mm                     |
| Diameter                    | 70 mm                     |
| Materials                   | PC                        |
| Dome colour                 | Blue                      |
| Protection category         | IP65                      |
| Service life optical        | 4 million flashes minimum |
| Working temperature minimum | -20°C                     |
| Working temperature maximum | +50°C                     |
| UL Type Rating              | Type 12                   |
| Weight with packaging       | 86 g                      |
| Product weight              | 71 g                      |

**ELECTRICAL DATA**

|                             |                          |
|-----------------------------|--------------------------|
| Operating voltage           | 230V                     |
| Operating voltage type      | AC                       |
| Operating voltage type      | 50Hz                     |
| Operating voltage tolerance | +/- 10%                  |
| Rated operational voltage   | 230 VAC                  |
| Rated operational current   | 15 mA                    |
| Rated inrush current        | 35 mA                    |
| Protection class            | Protection class 2       |
| Pollution degree            | 3                        |
| Overvoltage category        | II                       |
| Isolation voltage           | Ui = 250V; Uimp = 2.500V |

**OPTICAL DATA**

|                      |       |
|----------------------|-------|
| Light source         | Xenon |
| Light colour         | Blue  |
| Optical signal image | Flash |
| Flash frequency      | 1 Hz  |
| Flash output         | 2 J   |



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

KombiSIGN 71 / Flash Beacon 643

**Flashing light element 230VAC BU**

**DRAWING**



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.