



ODE-3-220105-1 F 4 A-01

Optidrive E3 Single Phase VFD Datasheet

1.1 kW, 10.5 A, 200-240 V, 1PH,
IP66 Outdoor Non-switched Variable Frequency Drive
with EMC Filter

Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	14 A
Supply Fuse or MCB (Type B)	20 A

Output Ratings

Motor Output Rating	1.1 kW
Output Voltage	0 – Supply Voltage
Output Current	10.5 A


Cable Information

Max Supply Cable Size	8 mm ²
Max Motor Cable Size	8 mm ²
Max motor cable length	100 m

Factory Build Options

EMC Filter	Internal EMC Filter
Brake Transistor	Internal Braking Transistor
Enclosure	IP66 Outdoor Non-switched

Installation Options & Peripherals



Dimensions

Size	2
Height	257 mm
Width	188 mm
Depth	187 mm
Weight	4.1 kg
Packaged Weight	4.6 kg
Fixings	4 x M4





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk