

Cuboid proximity switches (Varikont L)

(active surface facing forward)

Type	Installation	Installation diagrams					Dimensions [mm]	
		X	Y	Y	B	Y	X	
NBB20-L2...	flush	≥ 0	≥ 0	≥ 0	≥ 60	≥ 80	≥ 0	
NBN30-L2...	not flush	≥ 20	-	-	≥ 90	≥ 160	≥ 10	
NBN40-L2...	not flush	40	-	-	≥ 120	≥ 160	≥ 20	
NRB20-L3...	bündig	≥ 0	≥ 0	≥ 0	≥ 60	≥ 90	≥ 0	
NRN35-L3...	nicht bündig	≥ 35	-	-	≥ 105	≥ 200	≥ 15	
NRN40-L3K...	nicht bündig	40	-	-	≥ 120	≥ 300	≥ 20	

(active surface facing up)

Type	Installation	Installation diagrams					Dimensions [mm]			
		X	Y	Y	X	Y	X	Y		
NBB20-L2...	flush	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0	
NBN30-L2...	not flush	≥ 0	≥ 15	≥ 20	≥ 30 ≥ 40	≥ 5 ≥ 0	≥ 30 ≥ 40	≥ 10 ≥ 0		
NBN40-L2...	not flush	≥ 0	≥ 28	≥ 35	≥ 0	≥ 28	≥ 0	≥ 35		
NRB20-L3...	bündig	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0	≥ 0		
NRN35-L3...	nicht bündig	≥ 0	≥ 30	≥ 35	≥ 30 ≥ 40	≥ 20 ≥ 10	≥ 30 ≥ 40	≥ 30 ≥ 20		
NRN40-L3K...	nicht bündig	≥ 0	≥ 45	≥ 45	≥ 30 ≥ 40	≥ 20 ≥ 10	≥ 30 ≥ 40	≥ 30 ≥ 20		

Flat Pack switches (FP)

Type	Installation	Installation diagrams					Dimensions [mm]		
		X	Y	Y	B	Y	Y		
NCB40-FP...	flush	≥ 0	≥ 0	≥ 0	120	≥ 225	≥ 0		
NCN50-FP...	not flush	≥ 25	≥ 20	≥ 30	150	≥ 450	≥ 45		
NCB50-FP...	flush	≥ 5	≥ 0	≥ 0	150	≥ 250	≥ 5		
NJ40-FP...	not flush	≥ 40	≥ 0	≥ 0	120	≥ 150	≥ 20		
NJ50-FP...	not flush	≥ 40	≥ 20	≥ 0	150	≥ 240	≥ 45		
NRB50-FP...	flush	≥ 5	≥ 0	≥ 0	150	≥ 170	≥ 10		
NRN75-FP...	not flush	≥ 20	≥ 40	≥ 40	200	≥ 300	≥ 45		

In individual cases deviations are possible due to exemplary dispersion

(active surface facing forward, continuation)

X	Y	X	Y	X	
≥ 0	≥ 0	≥ 0	≥ 0	≥ 70	
≥ 15	≥ 10	≥ 15	≥ 25	≥ 140	
≥ 20	≥ 0	≥ 20	≥ 15	≥ 300	
≥ 30	≥ 10	≥ 30	≥ 15	≥ 130	
≥ 40	≥ 0	≥ 40	≥ 0	≥ 250	
≥ 0	≥ 0	≥ 0	≥ 0	≥ 300	
≥ 20	≥ 10	≥ 25	≥ 15		
≥ 30	≥ 0	≥ 30	≥ 0		
≥ 25	≥ 15	≥ 25	≥ 25		
≥ 40	≥ 0	≥ 40	≥ 0		

(active surface to the side)

	Type
X	
≥ 0	NBB20-L2...
-	NBN30-L2...
-	NBN40-L2...
≥ 0	NRB20-L3...
-	NRN35-L3...
-	NRN40-L3K...

(active surface facing up, continuation)

								Type
Y	Y	X	Y	X	Y			
≥ 5	≥ 10	≥ 0	≥ 5	≥ 0	≥ 10	NBB20-L2...		
≥ 20	≥ 25	≥ 30	≥ 10	≥ 30	≥ 15	NBN30-L2...		
		≥ 40	≥ 0	≥ 40	≥ 5			
≥ 36	≥ 42	≥ 0	≥ 36	≥ 0	≥ 42	NBN40-L2...		
≥ 5	≥ 10	≥ 0	≥ 5	≥ 0	≥ 10	NRB20-L3...		
≥ 35	≥ 40	≥ 30	≥ 20	≥ 30	≥ 30	NRN35-L3...		
		≥ 40	≥ 10	≥ 40	≥ 20			
≥ 45	≥ 50	≥ 30	≥ 20	≥ 30	≥ 30	NRN40-L3K...		
		≥ 40	≥ 10	≥ 40	≥ 20			

Flat Pack switches (FP), continuation

	Type
X	
≥ 290	NCB40-FP...
≥ 530	NCN50-FP...
≥ 240	NCB50-FP...
≥ 400	NJ40-FP...
≥ 500	NJ50-FP...
≥ 250	NRB50-FP...
≥ 560	NRN75-FP...

Mutual interference

To prevent the mutual interference between two similar sensors the minimum distances specified in these tables must be kept. For applications where these distances cannot be maintained proximity switches with offset frequencies are available upon request. These can then be installed directly adjacent.

Please talk to our product specialist.

Date of issue 2019-05-23



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk