

EU-Declaration of conformity

en/de

EU-Konformitätserklärung

Pepperl+Fuchs GmbH
 Lilienthalstraße 200
 68307 Mannheim
 Germany
 Phone +49 621 776-0
 Fax +49 621 776-1000

No. / Nr.: DOC-4016
 Date / Datum: 2018-10-09

Copyright Pepperl+Fuchs
 www.pepperl-fuchs.com



Declaration of conformity / Konformitätserklärung

We, Pepperl+Fuchs GmbH declare under our sole responsibility that the **products** listed below are in conformity with the listed **European Directives** and **standards**.

Die Pepperl+Fuchs GmbH erklärt hiermit in alleiniger Verantwortung, dass die unten gelisteten **Produkte** den genannten **Europäischen Richtlinien** und **Normen** entsprechen.

Productfamily / Produktfamilie

Productfamily / Produktfamilie	Item number	Description / Beschreibung
Prod.Fam. N*-6,5/8G*-*	304615-xxxx	Inductive sensor

The „X“ marked letters of the type code are placeholders and replaced by the code described in ANNEX TYPE CODE.

Die mit „X“ markierten Stellen im Typenschlüssel sind Platzhalter und können durch den Schlüssel ersetzt werden der in ANNEX TYPE CODE beschrieben ist.

Directives and Standards / Richtlinien und Normen

EU-Directive EU-Richtlinie	Standards Normen
EMC 2014/30/EU (L96/79-106)	EN 60947-5-2/A1:2012-11 EN 60947-5-2:2007-12
RoHS 2011/65/EU (L174/88-110)	EN 50581:2012-09

Affixed CE Marking / Angebrachte CE-Kennzeichnung



Signatures / Unterschriften

Mannheim, 2018-10-09

i.V. Ulrich Ehrenfried
 Manager Innovation Unit
 Electromagnetic Sensors

i.V. Thorsten Schieck
 Product Manager

■ ANNEX TYPE CODE

The „X“ marked letters of the type code are placeholders and replaced by the following code:

Die mit „X“ markierten Stellen im Typenschlüssel sind Platzhalter und können durch folgenden Schlüssel ersetzt werden:

Nxxxx-xxxxxxx-xx-xxx-xxx-xx-x																	
N	x	x	x	-	xx	xx	xx	-	xx	-	xxx	-	xxx	-	xx	-	Y
In- ductive sensor	B – Basic	Installation conditions	Nomi- nal sens- ing range in mm		Sensor diameter	Housing	Housing length, front face to end of thread in mm		Output stage		Cable length in m, if deviating to standard 2m, e.g.		Cable mate- rial, if deviat- ing to stand- ard PVC, e.g.		Connector		Customer specific
	E – Higher sensing range	B - flush		6,5 - 6,5mm	GM - threaded metal sleeve	E0 - 3-Wire DC NPN NO							V3 - M8 Connector				
	X – Special	N - non- flush		8 - 8,0mm	M – metal sleeve without thread	E1 - 3-Wire DC NPN NC			0,2M - 0,2m	PUR - PUR cable	V1 - M12 Connector						
					E2 - 3-Wire DC PNP NO			0,5M - 0,5m									
					E3 - 3-Wire DC PNP NC			5M - 5m									
									A0 - 4-Wire DC NPN complimen- tary NO/NC		10M - 10m						
									A2 - 4-Wire DC PNP complimen- tary NO/NC								
											Omitted if not applica- ble		Omitted if not applicable		Omitted if not applicable		Omitted if not applicable



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk