




### Model Number

NBN8-12GM50-E2-V1


### Features

- 8 mm non-flush
- Increased operating distance
- Extended temperature range

### Connection



### Pinout



Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 2 | WH | (white) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

### Accessories

#### BF 12

Mounting flange, 12 mm

#### V1-W

4-pin, M12 female field-attachable connector


#### V1-G-2M-PUR

Cable socket, M12, 4-pin, PUR cable

#### V1-W-2M-PUR

Cable socket, M12, 4-pin, PUR cable

### Dimensions



### Technical Data

#### General specifications

|                              |       |                                                                                                           |
|------------------------------|-------|-----------------------------------------------------------------------------------------------------------|
| Switching element function   | PNP   | NO                                                                                                        |
| Rated operating distance     | $s_n$ | 8 mm                                                                                                      |
| Installation                 |       | non-flush                                                                                                 |
| Output polarity              |       | DC                                                                                                        |
| Assured operating distance   | $s_a$ | 0 ... 6.48 mm ( -25 ... 70 °C ( -13 ... 158 °F ) )<br>0 ... 6.08 mm ( -40 ... -25 °C ( -40 ... -13 °F ) ) |
| Reduction factor $r_{Al}$    |       | 0.39                                                                                                      |
| Reduction factor $r_{Cu}$    |       | 0.3                                                                                                       |
| Reduction factor $r_{304}$   |       | 0.7                                                                                                       |
| Reduction factor $r_{Brass}$ |       | 0.45                                                                                                      |

#### Nominal ratings

|                                   |       |                            |
|-----------------------------------|-------|----------------------------|
| Operating voltage                 | $U_B$ | 10 ... 30 V                |
| Switching frequency               | $f$   | 0 ... 1500 Hz              |
| Hysteresis                        | $H$   | typ. 5%                    |
| Reverse polarity protected        |       | reverse polarity protected |
| Short-circuit protection          |       | pulsing                    |
| Voltage drop                      | $U_d$ | ≤ 3 V                      |
| Operating current                 | $I_L$ | 0 ... 200 mA               |
| No-load supply current            | $I_0$ | ≤ 16 mA                    |
| Indication of the switching state |       | Multihole-LED, yellow      |

#### Functional safety related parameters

|                          |        |
|--------------------------|--------|
| MTTF <sub>d</sub>        | 1560 a |
| Mission Time ( $T_M$ )   | 20 a   |
| Diagnostic Coverage (DC) | 0 %    |

#### Ambient conditions

|                     |                                  |
|---------------------|----------------------------------|
| Ambient temperature | -40 ... 70 °C ( -40 ... 158 °F ) |
|---------------------|----------------------------------|

#### Mechanical specifications

|                   |                                 |
|-------------------|---------------------------------|
| Connection type   | Device connector M12 x 1, 4-pin |
| Housing material  | brass, nickel-plated            |
| Sensing face      | PBT                             |
| Protection degree | IP67                            |

#### General information

|                   |                                          |
|-------------------|------------------------------------------|
| Scope of delivery | 2 self locking nuts in scope of delivery |
|-------------------|------------------------------------------|

#### Compliance with standards and directives

|                     |                                         |
|---------------------|-----------------------------------------|
| Standard conformity |                                         |
| Standards           | EN 60947-5-2:2007<br>IEC 60947-5-2:2007 |

#### Approvals and certificates

|              |                                                                                                                    |
|--------------|--------------------------------------------------------------------------------------------------------------------|
| UL approval  | cULus Listed, General Purpose                                                                                      |
| CSA approval | cCSAus Listed, General Purpose                                                                                     |
| CCC approval | Products with a maximum operating voltage of ≤36 V do not bear a CCC marking because they do not require approval. |