



### Model Number

NBB2-8GM30-E0

### Features

- 2 mm flush
- Increased operating distance
- Extended temperature range  
-40 ... +85 °C

### Accessories

#### BF 8

Mounting flange, 8 mm

#### EXG-08

Quick mounting bracket with dead stop

## Technical Data

### General specifications

|                              |       |   |
|------------------------------|-------|---|
| Switching function           |       | Normally open (NO)  |
| Output type                  |       | NPN   |
| Rated operating distance     | $s_n$ | 2 mm  |
| Installation                 |       | flush   |
| Output polarity              |       | DC  |
| Assured operating distance   | $s_a$ | 0 ... 1.62 mm   |
| Actuating element            |       | mild steel, e. g. 1.0037, SR235JR (formerly St37-2)<br>8 mm x 8 mm x 1 mm |
| Reduction factor $r_{Al}$    |       | 0.4   |
| Reduction factor $r_{Cu}$    |       | 0.3   |
| Reduction factor $r_{304}$   |       | 0.75  |
| Reduction factor $r_{Brass}$ |       | 0.45  |
| Output type                  |       | 3-wire  |

### Nominal ratings

|                                |       |                            |
|--------------------------------|-------|----------------------------|
| Operating voltage              | $U_B$ | 5 ... 30 V                 |
| Switching frequency            | $f$   | 0 ... 6000 Hz              |
| Hysteresis                     | $H$   | typ. 5%                    |
| Reverse polarity protection    |       | reverse polarity protected |
| Short-circuit protection       |       | pulsing                    |
| Voltage drop                   | $U_d$ | $\leq 1.5$ V               |
| Operating current              | $I_L$ | 0 ... 100 mA               |
| Off-state current              | $I_r$ | 0 ... 0.2 mA               |
| No-load supply current         | $I_0$ | $\leq 10$ mA               |
| Time delay before availability | $t_v$ | $\leq 100$ ms              |
| Switching state indicator      |       | LED, yellow                |

### Functional safety related parameters

|                          |       |
|--------------------------|-------|
| MTTF <sub>d</sub>        | 960 a |
| Mission Time ( $T_M$ )   | 20 a  |
| Diagnostic Coverage (DC) | 0 %   |

### Ambient conditions

|                     |                                |
|---------------------|--------------------------------|
| Ambient temperature | -40 ... 85 °C (-40 ... 185 °F) |
| Storage temperature | -40 ... 85 °C (-40 ... 185 °F) |

### Mechanical specifications

|                      |                       |
|----------------------|-----------------------|
| Connection type      | cable PVC , 2 m       |
| Core cross-section   | 0.14 mm <sup>2</sup>  |
| Housing material     | brass, nickel-plated  |
| Sensing face         | LCP                   |
| Degree of protection | IP67                  |
| Cable                |                       |
| Cable diameter       | 3.5 mm $\pm$ 0.1 mm   |
| Bending radius       | > 10 x cable diameter |

### General information

|                   |                     |
|-------------------|---------------------|
| Scope of delivery | 2 hex nuts included |
|-------------------|---------------------|


### Compliance with standards and directives

|                     |   |
|---------------------|---|
| Standard conformity |   |
| Standards           | EN 60947-5-2:2007<br>EN 60947-5-2/A1:2012<br>IEC 60947-5-2:2007<br>IEC 60947-5-2 AMD 1:2012 |


### Approvals and certificates

|              |  |
|--------------|--|
| UL approval  | cULus Listed, General Purpose, Class 2 Power Source                |
| CCC approval | CCC approval / marking not required for products rated $\leq 36$ V |

## Dimensions



Electrical Connection



Release date: 2019-07-03 08:51 Date of issue: 2019-07-03 304615-0035\_eng.xml



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)