



## Model Number

NJ2-11-SN-G

## Features

- 2 mm flush
- Usable up to SIL 3 acc. to IEC 61508
- ATEX approval Ex-i and Ex-na/tc for zone 0-2 and zone 20-22
- Degree of protection IP68

## Application



### Danger!

In safety-related applications the sensor must be operated with a qualified fail safe interface from Pepperl+Fuchs, such as KFD2-SH-EX1. Consider the "exida Functional Safety Assessment" document which is available on [www.pepperl-fuchs.com](http://www.pepperl-fuchs.com) as an integral part of this product's documentation.

## Technical Data

### General specifications

Switching function	Normally closed (NC)
Output type	NAMUR with safety function
Rated operating distance	$s_n$ 2 mm
Installation	flush
Assured operating distance	$s_a$ 0 ... 1.62 mm
Reduction factor $r_{AI}$	0.4
Reduction factor $r_{Cu}$	0.3
Reduction factor $r_{304}$	0.85
Safety Integrity Level (SIL)	up to SIL3 acc. to IEC 61508 <b>Danger!</b> In safety-related applications the sensor must be operated with a qualified fail safe interface from Pepperl+Fuchs, such as KFD2-SH-EX1. Consider the "exida Functional Safety Assessment" document which is available on <a href="http://www.pepperl-fuchs.com">www.pepperl-fuchs.com</a> as an integral part of this product's documentation.
Output type	2-wire

### Nominal ratings

Nominal voltage	$U_o$ 8.2 V
Switching frequency	$f$ 0 ... 3000 Hz
Suitable for 2:1 technology	yes, with reverse polarity protection diode
Current consumption	
Measuring plate not detected	$\geq 3$ mA
Measuring plate detected	$\leq 1$ mA

### Functional safety related parameters

Safety Integrity Level (SIL)	SIL 3
MTTF <sub>d</sub>	10660 a
Mission Time (T <sub>M</sub> )	20 a
Diagnostic Coverage (DC)	0 %

### Ambient conditions

Ambient temperature	-40 ... 100 °C (-40 ... 212 °F)
---------------------	---------------------------------

### Mechanical specifications

Connection type	cable silicone, 2 m
Core cross-section	0.34 mm <sup>2</sup>
Housing material	stainless steel (303/1.4305)
Sensing face	Valox (PBT), black
Degree of protection	IP68
Cable	
Bending radius	> 10 x cable diameter

### General information

Use in the hazardous area	see instruction manuals
---------------------------	-------------------------


### Compliance with standards and directives

Standard conformity	
NAMUR	EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards	EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012


### Approvals and certificates

EAC conformity	TR CU 012/2011
FM approval	
Control drawing	116-0165
UL approval	cULus Listed, General Purpose
Ordinary Location	E87056
Hazardous Location	E501628
Control drawing	116-0454
CCC approval	CCC approval / marking not required for products rated $\leq 36$ V

## Dimensions



Electrical Connection



Release date: 2019-08-27 16:48 Date of issue: 2019-08-27 250952\_eng.xml

**Data for application in connection with hazardous areas**

Equipment protection level Ga , Gb , Gc (nA) , Da , Dc , Mb

**Equipment protection level Ga**

Type of protection intrinsic safety  
 CE marking **CE**0102

**Certificates**

Appropriate type NJ 2-11-SN-G...  
 ATEX certificate PTB 00 ATEX 2049 X  
 ATEX marking **Ex** II 1G Ex ia IIC T6...T1 Ga  
 Standards EN 60079-0:2012+A11:2013 , EN 60079-11:2012  
 IECEx certificate IECEx PTB 11.0092X  
 IECEx marking Ex ia IIC T6...T1 Ga  
 Standards IEC 60079-0:2011 , IEC 60079-11:2011

Effective internal capacitance  $C_i$   $\leq 50 \mu F$   
 A cable length of 10 m is considered.  
 Effective internal inductance  $L_i$   $\leq 150 \mu H$   
 A cable length of 10 m is considered.

Maximum permissible ambient temperature  $T_{amb}$  Also observe the maximum permissible ambient temperature stated in the general technical data.  
 Keep to the lower of the two values.

for ATEX  
 at  $U_i = 16 V$  ,  $I_i = 25 mA$  ,  $P_i = 34 mW$  ,  
 T6 : 59 °C (138.2 °F)  
 T5 : 71 °C (159.8 °F)  
 T4 : 99 °C (210.2 °F)  
 T3 : 99 °C (210.2 °F)  
 T2 : 99 °C (210.2 °F)  
 T1 : 99 °C (210.2 °F)  
 at  $U_i = 16 V$  ,  $I_i = 25 mA$  ,  $P_i = 64 mW$  ,  
 T6 : 56 °C (132.8 °F)  
 T5 : 68 °C (154.4 °F)  
 T4 : 96 °C (204.8 °F)  
 T3 : 96 °C (204.8 °F)  
 T2 : 96 °C (204.8 °F)  
 T1 : 96 °C (204.8 °F)  
 at  $U_i = 16 V$  ,  $I_i = 52 mA$  ,  $P_i = 169 mW$  ,  
 T6 : 45 °C (113 °F)  
 T5 : 57 °C (134.6 °F)  
 T4 : 81 °C (177.8 °F)  
 T3 : 81 °C (177.8 °F)  
 T2 : 81 °C (177.8 °F)  
 T1 : 81 °C (177.8 °F)  
 at  $U_i = 16 V$  ,  $I_i = 76 mA$  ,  $P_i = 242 mW$  ,  
 T6 : 37 °C (98.6 °F)  
 T5 : 49 °C (120.2 °F)  
 T4 : 63 °C (145.4 °F)  
 T3 : 63 °C (145.4 °F)  
 T2 : 63 °C (145.4 °F)  
 T1 : 63 °C (145.4 °F)

for IECEx  
 at  $U_i = 16 V$  ,  $I_i = 25 mA$  ,  $P_i = 34 mW$  ,  
 T6 : 76 °C (168.8 °F)  
 T5 : 91 °C (195.8 °F)  
 T4 : 100 °C (212 °F)  
 T3 : 100 °C (212 °F)  
 T2 : 100 °C (212 °F)  
 T1 : 100 °C (212 °F)  
 at  $U_i = 16 V$  ,  $I_i = 25 mA$  ,  $P_i = 64 mW$  ,  
 T6 : 73 °C (163.4 °F)  
 T5 : 88 °C (190.4 °F)  
 T4 : 100 °C (212 °F)  
 T3 : 100 °C (212 °F)  
 T2 : 100 °C (212 °F)  
 T1 : 100 °C (212 °F)  
 at  $U_i = 16 V$  ,  $I_i = 52 mA$  ,  $P_i = 169 mW$  ,  
 T6 : 62 °C (143.6 °F)  
 T5 : 77 °C (170.6 °F)  
 T4 : 81 °C (177.8 °F)  
 T3 : 81 °C (177.8 °F)  
 T2 : 81 °C (177.8 °F)  
 T1 : 81 °C (177.8 °F)  
 at  $U_i = 16 V$  ,  $I_i = 76 mA$  ,  $P_i = 242 mW$  ,  
 T6 : 54 °C (129.2 °F)  
 T5 : 63 °C (145.4 °F)  
 T4 : 63 °C (145.4 °F)  
 T3 : 63 °C (145.4 °F)  
 T2 : 63 °C (145.4 °F)  
 T1 : 63 °C (145.4 °F)

Release date: 2019-08-27 16:48 Date of issue: 2019-08-27 250952\_eng.xml

**Equipment protection level Gb**

Type of protection	intrinsic safety	
CE marking	CE 0102	
<b>Certificates</b>		
Appropriate type	NJ 2-11-SN-G...	
ATEX certificate	PTB 00 ATEX 2049 X	
ATEX marking	Ex II 1G Ex ia IIC T6...T1 Ga	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
IECEX certificate	IECEX PTB 11.0092X	
IECEX marking	Ex ia IIC T6...T1 Ga	
Standards	IEC 60079-0:2011 , IEC 60079-11:2011	
Effective internal capacitance	$C_i$	$\leq 50$ nF A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 150$ $\mu$ H A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW , T6 : 76 °C (168.8 °F) T5 : 91 °C (195.8 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW , T6 : 73 °C (163.4 °F) T5 : 88 °C (190.4 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW , T6 : 62 °C (143.6 °F) T5 : 77 °C (170.6 °F) T4 : 81 °C (177.8 °F) T3 : 81 °C (177.8 °F) T2 : 81 °C (177.8 °F) T1 : 81 °C (177.8 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW , T6 : 54 °C (129.2 °F) T5 : 63 °C (145.4 °F) T4 : 63 °C (145.4 °F) T3 : 63 °C (145.4 °F) T2 : 63 °C (145.4 °F) T1 : 63 °C (145.4 °F)	

**Equipment protection level Gc (nA)**

Type of protection	"n"	
CE marking	CE	
<b>Certificates</b>		
ATEX certificate	PF 15 CERT 3754 X	
ATEX marking	Ex II 3G Ex nA IIC T6 Gc	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-15:2010	
Possible characteristics	maximum operating voltage $U_{Bmax}$ , maximum load current $I_{Lmax}$ , minimum series resistance $R_V$ , maximum analog output voltage $U_{Amax}$ , maximum analog output current $I_{Amax}$	
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. using an amplifier in accordance with EN 60947-5-6 : 61 °C (141.8 °F) at $U_{Bmax} = 9$ V , $R_V = 562$ $\Omega$ : 61 °C (141.8 °F)	

**Equipment protection level Da**

Type of protection	intrinsic safety	
CE marking	CE 0102	
<b>Certificates</b>		
Appropriate type	NJ 2-11-SN-G...	
ATEX certificate	PTB 00 ATEX 2049 X	
ATEX marking	Ex II 1D Ex ia IIIC T135°C Da	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-11:2012	
IECEX certificate	IECEX PTB 11.0092X	
IECEX marking	Ex ia IIIC T135°C Da	
Standards	IEC 60079-0:2011 , IEC 60079-11:2011	
Effective internal capacitance	$C_i$	$\leq 50$ nF A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 150$ $\mu$ H A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW : 81 °C (177.8 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW : 63 °C (145.4 °F)	

**Equipment protection level Dc**

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.comUSA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.comGermany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.comSingapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

Type of protection	Protection by enclosure "tc"	
CE marking	CE	
<b>Certificates</b>		
ATEX certificate	PF 15 CERT 3774 X	
ATEX marking	Ⓔ II 3D Ex tc IIIC T80 °C Dc	
Standards	EN 60079-0:2012+A11:2013 , EN 60079-31:2014	
Possible characteristics	maximum operating voltage $U_{Bmax}$ , maximum load current $I_{Lmax}$ , minimum series resistance $R_V$ , maximum analog output voltage $U_{Amax}$ , maximum analog output current $I_{Amax}$	
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. using an amplifier in accordance with EN 60947-5-6 : 61 °C (141.8 °F) at $U_{Bmax} = 9 V$ , $R_V = 562 \Omega$ : 61 °C (141.8 °F)	
<b>Equipment protection level Mb</b>		
Type of protection	intrinsic safety	
<b>Certificates</b>		
Appropriate type	NJ 2-11-SN-G...	
IECEX certificate	IECEX PTB 11.0092X	
IECEX marking	Ex ia I Mb	
Standards	IEC 60079-0:2011 , IEC 60079-11:2011	
Effective internal capacitance	$C_i$	$\leq 50 \text{ nF}$ A cable length of 10 m is considered.
Effective internal inductance	$L_i$	$\leq 150 \mu\text{H}$ A cable length of 10 m is considered.
Maximum permissible ambient temperature $T_{amb}$	Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16 V$ , $I_i = 25 \text{ mA}$ , $P_i = 34 \text{ mW}$ : 100 °C (212 °F) at $U_i = 16 V$ , $I_i = 25 \text{ mA}$ , $P_i = 64 \text{ mW}$ : 100 °C (212 °F) at $U_i = 16 V$ , $I_i = 52 \text{ mA}$ , $P_i = 169 \text{ mW}$ : 81 °C (177.8 °F) at $U_i = 16 V$ , $I_i = 76 \text{ mA}$ , $P_i = 242 \text{ mW}$ : 63 °C (145.4 °F)	



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)