


USER FRIENDLY LIKE NO OTHER MINIATURE PHOTOELECTRIC SENSORS SERIES ML100



MINIATURE PHOTOELECTRIC SENSORS SERIES ML100

ML100 – USER FRIENDLY LIKE NO OTHER



POWERBEAM: THE RIGHT LIGHT SPOT FOR THE RIGHT APPLICATION

- Photoelectric sensors with PowerBeam use the most modern LED technology
- Best light spot for a variety of applications
- Uniform light spot provides excellent visibility with no central bond spot
- Best alignment capability over the entire operating range
- Light spot visibility optimized for human vision

CLEAR INDICATION OF OPERATING STATUS

- Excellent visibility of the status LEDs from long distances and different directions
- Power and switching status with weak signal indication
- Clear feedback of sensor status

GENERAL FEATURES

- General-purpose photoelectric sensors series ML100
- Miniature rectangular housing
- All basic photoelectric functions
- Metal M3 x 0.5 threaded mounting holes
- Sensitivity adjuster
- Light on / Dark on switch
- Very low current consumption
- Suitable for cold storage applications
- Protection against mutual interference
- Polarization reliably detects shiny objects
- Insensitive to ambient lighting
- Shock and vibration resistant

TYPES

ML100-8-H

Background suppression sensor with sensing range of 350 mm

ML100-8-H-100

Background suppression sensor with multiple light spots and sensing range of 100 mm

ML100-8-HW

Background evaluation sensor with sensing range of 350 mm

ML100-8

Diffuse mode sensor with sensing range of 1000 mm

ML100-8-W

Diffuse mode sensor with wide light spot and sensing range of 200 mm




ML100-55

Polarized retroreflective sensor with detection range of 7 m on small reflectors (50 x 50 mm)

M100/MV100

Thru-beam sensor with detection range of 30 m

Retroreflective and thru-beam sensors provide a more visible and larger light spot for easiest alignment, greatest detection range, and best stability control.



TECHNICAL DATA · ACCESSORIES

TECHNICAL DATA

Detection range	Retroreflective sensor Thru-beam sensor	0 m ... 7 m 0 m ... 30 m
Sensing range	Diffuse mode sensor Diffuse mode sensor with wide light spot Background suppression sensor Background suppression sensor with multiple light spots Background evaluation sensor	0 m ... 1000 mm 0 mm ... 200 mm 5 mm ... 350 mm 20 mm ... 100 mm 5 mm ... 350 mm
Light source	red light, 640 nm	
Angle of divergence	± 2°	
Indicator – LEDs	green: Power-On, yellow: object detected, stability control	
Operating elements	potentiometer for light on/dark on and sensitivity adjustment	
Operating voltage	10 V DC ... 30 V DC, class 2	
Current consumption	< 20 mA	
Switching type	light on/dark on, switchable	
Signal output	NPN, PNP	
Switching frequency	1000 Hz / 500 Hz / 250 Hz	
Response time	0,5 ms / 1 ms / 2 ms	
Ambient temperature	-30 °C ... 60 °C	
Protection degree	IP67	
Connection	fixed cable, M8 connector, Pigtail M8 and M12	




ACCESSORIES

CORDSETS

V31-GM-2M-PVC	straight connection, M8, 4-pin with 2 m PVC cable
V31-WM-2M-PVC	right-angle connection, 90° M8, 4-pin with 2 m PVC cable
V31-GM-2M-PUR	straight connection, M8, 4-pin with 2 m cable
V31-WM-2M-PUR	right-angle connection, 90° M8, 4-pin with 2 m cable
V1-W-2M-PUR	straight connection, M12, 4-pin with 2 m PVC cable
V1-G-2M-PVC	right-angle connection, 90° M12, 4-pin with 2 m PVC cable
V1-W-2M-PVC	straight connection, M12, 4-pin with 2 m cable
V1-G-2M-PUR	right-angle connection, 90° M12, 4-pin with 2 m cable

REFLECTORS

- Reflector H50 (50 mm x 50 mm)
Reference reflector
- Reflector H60 (40 mm x 60 mm)
- Reflector H85-2 (85 mm x 85 mm)



STANDARD MOUNTING BRACKET FOR SERIES ML100

OMH-10 – mounting bracket

Contact

Pepperl+Fuchs GmbH
Lilienthalstraße 200
68307 Mannheim · Germany
Tel. +49 621 776-4411 · Fax +49 621 776-27-4411
E-mail: fa-info@pepperl-fuchs.com

Worldwide Headquarters

Pepperl+Fuchs GmbH · Mannheim · Germany
E-mail: fa-info@pepperl-fuchs.com

USA Headquarters

Pepperl+Fuchs Inc. · Twinsburg · USA
E-mail: fa-info@us.pepperl-fuchs.com

Asia Pacific Headquarters

Pepperl+Fuchs Pte Ltd · Singapore
Company Registration No. 1999003130E
E-mail: fa-info@sg.pepperl-fuchs.com

www.pepperl-fuchs.com

 **PEPPERL+FUCHS**
SENSING YOUR NEEDS



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk