

**Certificate Number**  
**Baseefa06ATEX0040**  
**Issue 3**



**Issued 10 April 2018**  
**Page 1 of 4**

## 1 EU - TYPE EXAMINATION CERTIFICATE

2 **Safety Device, Controlling Device or Regulating Device intended for use outside a potentially explosive atmosphere but required for or contributing to the safe functioning of Equipment and Protective Systems with respect to the risks of explosion**  
**Directive 2014/34/EU**

3 EU - Type Examination Certificate **Baseefa06ATEX0040 – Issue 3**  
 Number:

3.1 In accordance with Article 41 of Directive 2014/34/EU, EC-Type Examination Certificates referring to 94/9/EC that were in existence prior to the date of application of 2014/34/EU (20 April 2016) may be referenced as if they were issued in accordance with Directive 2014/34/EU. Supplementary Certificates to such EC-Type Examination Certificates, and new issues of such certificates, may continue to bear the original certificate number issued prior to 20 April 2016.

4 Product: **Type KFD2-VR2-Ex1.50M/500M Transformer Isolated Voltage Repeater**

5 Manufacturer: **Pepperl + Fuchs GmbH**

6 Address: **Lilienthalstrasse 200, 68307 Mannheim, Germany**

7 This re-issued certificate extends EC Type Examination Certificate No. Baseefa06ATEX0040 to apply to product designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.

8 SGS Baseefa, Notified Body number 1180, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report No. **See Certificate Schedule**

9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

**EN 60079-0:2012+A11:2013 EN 60079-11:2012**

except in respect of those requirements listed at item 18 of the Schedule.

10 If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.

11 This EU - TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.

12 The marking of the product shall include the following :

⊕ II (1) G [Ex ia Ga] IIC (-20°C ≤ Ta ≤ +60°C)

⊕ II (1) D [Ex ia Da] IIIC (-20°C ≤ Ta ≤ +60°C)

⊕ I (M1) [Ex ia Ma] I (-20°C ≤ Ta ≤ +60°C)

SGS Baseefa Customer Reference No. **0808**

Project File No. **17/0737**

This document is issued by the Company subject to its General Conditions for Certification Services accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and the Supplementary Terms and Conditions accessible at <http://www.sgs.com/SGSBaseefa/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


### SGS Baseefa Limited

Rockhead Business Park, Staden Lane,  
 Buxton, Derbyshire SK17 9RZ

Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601  
 e-mail [baseefa@sgs.com](mailto:baseefa@sgs.com) web site [www.sgs.co.uk/sgsbaseefa](http://www.sgs.co.uk/sgsbaseefa)

Registered in England No. 4305578.

Registered address: Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN

  
 R S SINCLAIR  
 TECHNICAL MANAGER  
 On behalf of SGS Baseefa Limited

ABELLMAN  
 Certification  
 Manager

Certificate Number  
Baseefa06ATEX0040  
Issue 3



Issued 10 April 2018  
Page 2 of 4

13

## Schedule

14

Certificate Number Baseefa06ATEX0040 – Issue 3

### 15 Description of Product

The Type KFD2-VR2-Ex1.50M/500M Transformer Isolated Voltage Repeater is used to restrict the transfer of energy in the form of a low voltage analogue signal from unspecified non-hazardous area apparatus to intrinsically safe circuits located in a hazardous area. It also provides galvanic isolation between the hazardous area and non-hazardous area circuits.

The Type KFD2-VR2-Ex1.50M/500M Transformer Isolated Voltage Repeater comprises a number of electrical components, including two isolating transformers, fuses, resistors and zener diodes all mounted onto a single printed circuit board (PCB) and housed within a plastic enclosure with plug-in terminals.

#### Input/Output Parameters

##### Non-hazardous Area Terminals 1 & 14 wrt 2 & 15 and 7 wrt 8

$$U_m = 253V$$

The apparatus is designed to operate from a d.c. supply of up to 40V on the above terminals.

##### Hazardous Area Terminals 4 wrt 5

$$\begin{aligned} U_o &= 5.5V & C_o &= 58\mu F \\ I_o &= 2.4mA & L_o &= 1000mH \\ P_o &= 3.3mW \\ C_i &= 0 \\ L_i &= 0 \end{aligned}$$

The capacitance and either the inductance or inductance to resistance ratio (L/R) of the load connected to output terminals of the apparatus must not exceed the following values:

##### Hazardous Area Terminals 4 wrt 5

GROUP	CAPACITANCE ( $\mu F$ )	INDUCTANCE (mH)	OR	L/R RATIO ( $\mu H/ohm$ )
IIC	58	1000		425
IIB/IIIC	1000	1000		425
IIA	1000	1000		425
I	1000	1000		425

The above parameters apply when one of the two conditions below is given:

- the total  $L_i$  of the external circuit (excluding the cable) is  $< 1\%$  of the  $L_o$  value or
- the total  $C_i$  of the external circuit (excluding the cable) is  $< 1\%$  of the  $C_o$  value.

The above parameters are reduced to 50% when both of the two conditions below are given:

- the total  $L_i$  of the external circuit (excluding the cable)  $\geq 1\%$  of the  $L_o$  value and
- the total  $C_i$  of the external circuit (excluding the cable)  $\geq 1\%$  of the  $C_o$  value.

Note: the reduced capacitance of the external circuit (including cable) shall not be greater than  $1\mu F$  for Groups I, IIA & IIB/IIIC and  $600nF$  for Group IIC.

**Certificate Number**  
**Baseefa06ATEX0040**  
**Issue 3**



**Issued 10 April 2018**  
**Page 3 of 4**

## 16 Report Number

See Certificate History

## 17 Specific Conditions of Use

None

## 18 Essential Health and Safety Requirements

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9, the following are considered relevant to this product:

Clause	Subject	Compliance
1.2.7	LVD type requirements	Manufacturer responsibility
1.2.8	Overloading of equipment (protection relays, etc.)	User/Installer responsibility
1.4.1	External effects	User/Installer responsibility
1.4.2	Aggressive substances, etc.	User/Installer responsibility

## 19 Drawings and Documents

New drawings submitted for this issue of certificate:

Number	Sheet	Issue	Date	Description
266-012BS-C	1 of 1	C	2017-Sep-20	Summary
266-012BS-02B	1 of 1	B	2017-Sep-20	Safety relevant components
266-010BS-04F	1 – 15	F	2016-Mar-23	Mechanical Parts
266-012BS-06A	1 & 2	A	2017-Sep-20	Transformer details
266-012BS-10C	1 – 3	C	2017-Sep-20	Type Label

Current drawings which remain unaffected by this issue:

Number	Sheet	Issue	Date	Description
266-012BS-01A	1 & 2	-	2008-Dec-02	Schematic
266-012BS-03A	1 of 1	-	2008-Dec-02	Component overlay
266-012BS-05A	1 – 6	-	2008-Dec-02	Main printed circuit board

These drawings are common to, and held with, IECEx BAS 06.0011.

## 20 Certificate History

Certificate No.	Date	Comments
Baseefa06ATEX0040	8 March 2006	The release of the prime certificate. The associated test and assessment is documented in Test Report No. 05(C)0664.
Baseefa06ATEX0040/1	29 September 2009	To permit changes to the schematic and PCB to introduce the Type KFD2-VR2-Ex1.500M.  To confirm that the equipment covered by this certificate has been reviewed against the requirements of EN 60079-0:2006 and EN 60079-11:2007 in respect of the differences from EN 60079-0:2000 and EN 60079-11:1999 and that none of these differences affect this equipment.  The equipment is also considered suitable for Group I applications and has additionally been assessed against the relevant requirements

**Certificate Number**  
**Baseefa06ATEX0040**  
**Issue 3**



**Issued 10 April 2018**  
**Page 4 of 4**

Certificate No.	Date	Comments
		<p>of EN 61241-11:2006 and the following additional marking may be applied:</p> <p>⊕ I (M1) [Ex ia] I            ⊕ II (1)D [Ex iaD]</p> <p>Report No. GB/BAS/ExTR09.0009/00. Project File No. 08/0921.</p>
Baseefa06ATEX0040 Issue 2	7 July 2015	<p>This issue incorporates previously issued primary and supplementary certificates into one certificate, permits changes to the transformer and confirms that the equipment covered by this certificate has been reviewed against the requirements of EN 60079-0:2012+A11:2013 and EN 60079-11:2012 in respect of the differences from EN 60079-0:2006 and EN 60079-11:2007 and that none of these differences, with the exception of marking, affect this equipment. The equipment is now marked:</p> <p>⊕ II (1)G [Ex ia Ga] IIC            ⊕ II (1)D [Ex ia Da] IIIC            ⊕ I (M1) [Ex ia Ma] I</p> <p>Test Report No. GB/BAS/ExTR15.0021/00            Project File No. 15/0067.</p>
Baseefa06ATEX0040 Issue 3	10 April 2018	<p>To permit the introduction of alternative components and the use of an alternative housing material.</p> <p>Test Report No. GB/BAS/ExTR18.0075/00            Project File No. 17/0737.</p>
For drawings applicable to each issue, see original of that issue.		



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)