

Product datasheet

Characteristics

A9E18322

Acti9 iIL single indicator light - White - 110-230
Vac



Main

| | |
|---------------------------|--|
| Range of product | Acti 9 |
| Product name | Acti 9 iIL |
| Product or component type | Modular pilot lighth |
| Device short name | IIL |
| [Us] rated supply voltage | 110...230 V AC at 50/60 Hz 110...130 V DC |

Complementary

| | |
|--|---|
| Flashing frequency | 2 Hz |
| Indicator light | 1 LED white, service life 100000 h of constant lighting efficiency (consumption 0.3 W) |
| Mounting mode | Fixed |
| Mounting support | Symmetrical DIN rail |
| Comb busbar and distribution block compatibility | Upside: ProDis |
| 9 mm pitches | 2 |
| Height | 82 mm |
| Width | 18 mm |
| Depth | 69.5 mm |
| Colour | White (RAL 9003) |
| Auxiliary connection terminal | Tunnel type terminal 1 cable(s) rigid 0.5 mm ² Tunnel type terminal 2 cable(s) rigid 2.5 mm ² Tunnel type terminal 1 cable(s) flexible 0.5 mm ² Tunnel type terminal 2 cable(s) flexible 2.5 mm ² Tunnel type terminal 2 cable(s) flexible with ferrule 2.5 mm ² |
| Wire stripping length | 9 mm |
| Tightening torque | 1 N.m |

Environment

| | |
|-----------|---------------|
| Standards | IEC 60947-5-1 |
|-----------|---------------|

Feb 27, 2020

| | |
|---------------------------------------|---------------|
| IP degree of protection | IP2 IPxx B |
| Pollution degree | 3 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage | -40...80 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk