

Product datasheet

Characteristics

A9N21553

iDPN - circuit breaker - iDPN N - 1P + N - 2A - C curve



Main

Range of product	Clario
Range	Clario
Product name	IDPN
Product or component type	Miniature circuit-breaker
Device short name	IDPN N
Device application	Distribution
Poles description	1P + N
Number of protected poles	1
Neutral position	Left
[In] rated current	2 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	10 kA I _{cu} at 230 V AC 50/60 Hz conforming to IEC 60947-2 6000 A I _{cn} at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1
Suitability for isolation	Yes

Complementary

Network frequency	50/60 Hz
[U _e] rated operational voltage	230 V AC 50/60 Hz between phase and neutral
Magnetic tripping limit	5...10 x I _n
[I _{cs}] rated service breaking capacity	6000 A 100 % x I _{cn} at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1 7.5 kA 75 % x I _{cn} at 230 V AC 50/60 Hz conforming to IEC 60947-2
Limitation class	3 conforming to EN/IEC 60898-1
[U _i] rated insulation voltage	400 V AC 50/60 Hz conforming to IEC 60947-2
[U _{imp}] rated impulse withstand voltage	4 kV conforming to IEC 60947-2
Contact position indicator	Yes
Control type	Toggle

Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	78 mm
Net weight	115 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	20000 cycles
Locking options description	Padlocking device
Connections - terminals	Tunnel type terminals downstream 0.33...10 mm ² flexible Tunnel type terminals downstream 0.75...16 mm ² rigid Tunnel type terminals upstream 0.33...10 mm ² flexible Tunnel type terminals upstream 0.75...16 mm ² rigid
Wire stripping length	13 mm
Tightening torque	2 N.m
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60898-1 EN/IEC 60947-2
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947-1
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk