

Product datasheet

Characteristics

CCT15365

Acti 9 - IH - mechanical time switch - 24 h - 200 h memory



Main

Range of product	Acti 9
Product name	Acti 9 IH
Device short name	IH
Product or component type	Mechanical time switch
Number of channels	1
Function available	Manual time changeover

Complementary

Device application	Building
Load type	230 V AC halogen lamp (1100 W) 230 V AC incandescent lamp (1100 W) dual mounted fluorescent tube conventional ballast (2 x 100 W) dual mounted fluorescent tube conventional ballast (2 x 58 W) non-corrected fluorescent tube conventional ballast (100 W) non-corrected fluorescent tube conventional ballast (40 W) non-corrected fluorescent tube conventional ballast (58 W) parallel-corrected fluorescent tube conventional ballast (40 W) parallel-corrected fluorescent tube conventional ballast (58 W) serial-corrected fluorescent tube conventional ballast (100 W) serial-corrected fluorescent tube conventional ballast (40 W) serial-corrected fluorescent tube conventional ballast (58 W)
Cycle duration	24 h
Measurement accuracy	+/- 1 s/day
Maximum number of switchings	48 on - 48 off
Minimum interval duration	15 min
Type of setting	Manual time changeover
Measurement accuracy	+/- 1 s/day 20 °C
Power consumption in VA	2.5 VA
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
Battery life	6 year(s)

Backup time	200 h time and program saving 230 V AC 100 h time and program saving 100 V AC
Mounting support	DIN rail
9 mm pitches	6
Colour tint	White (RAL 9003)
Connections - terminals	Screwless terminals
IP degree of protection	IP20 B
Width	54 mm
Height	90 mm
Depth	66 mm
Net weight	0.198 kg

Environment

Ambient air temperature for operation	-20...55 °C
IP degree of protection	Terminals: IP20 B

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk