

# Product datasheet

## Characteristics

# A9R61240

Acti 9 iID - RCCB - 2P - 40A - 30mA - type A-SI



### Main

|                                     |                                         |
|-------------------------------------|-----------------------------------------|
| Range                               | Acti 9                                  |
| Product name                        | Acti 9 iID                              |
| Product or component type           | Residual current circuit breaker (RCCB) |
| Device short name                   | iID                                     |
| Poles description                   | 2P                                      |
| Neutral position                    | Left                                    |
| [In] rated current                  | 40 A                                    |
| Network type                        | AC                                      |
| Earth-leakage sensitivity           | 30 mA                                   |
| Earth-leakage protection time delay | Instantaneous                           |
| Earth-leakage protection class      | Type A-SI                               |

### Complementary

|                                         |                                                 |
|-----------------------------------------|-------------------------------------------------|
| Device location in system               | Outgoer                                         |
| Network frequency                       | 50/60 Hz                                        |
| [Ue] rated operational voltage          | 220...240 V AC 50/60 Hz                         |
| Residual current tripping technology    | Voltage independent                             |
| Rated breaking and making capacity      | I <sub>dm</sub> 1500 A<br>I <sub>m</sub> 1500 A |
| Rated conditional short-circuit current | 10 kA                                           |
| [Ui] rated insulation voltage           | 500 V AC 50/60 Hz                               |
| [Uimp] rated impulse withstand voltage  | 6 kV                                            |
| Contact position indicator              | Yes                                             |
| Control type                            | Toggle                                          |
| Mounting mode                           | Clip-on                                         |
| Mounting support                        | DIN rail                                        |
| 9 mm pitches                            | 4                                               |
| Height                                  | 91 mm                                           |
| Width                                   | 36 mm                                           |

|                             |                                                                                                                                                                                                                              |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Depth                       | 73.5 mm                                                                                                                                                                                                                      |
| Net weight                  | 0.21 kg                                                                                                                                                                                                                      |
| Colour                      | White                                                                                                                                                                                                                        |
| Mechanical durability       | 20000 cycles                                                                                                                                                                                                                 |
| Electrical durability       | AC-1: 15000 cycles                                                                                                                                                                                                           |
| Locking options description | Padlocking device                                                                                                                                                                                                            |
| Connections - terminals     | Single terminal top or bottom 1...35 mm <sup>2</sup> rigid<br>Single terminal top or bottom 1...25 mm <sup>2</sup> flexible<br>Single terminal top or bottom 1...25 mm <sup>2</sup> flexible with ferrule<br>Single terminal |
| Wire stripping length       | 14 mm for top or bottom connection                                                                                                                                                                                           |
| Tightening torque           | 3.5 N.m top or bottom                                                                                                                                                                                                        |

## Environment

|                                       |                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------|
| Standards                             | EN/IEC 61008-1                                                                   |
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree                      | 3                                                                                |
| Electromagnetic compatibility         | 8/20 µs impulse withstand, 3000 A conforming to EN/IEC 61008-1                   |
| Ambient air temperature for operation | -25...60 °C                                                                      |
| Ambient air temperature for storage   | -40...85 °C                                                                      |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)