


# Product datasheet

## Characteristics

# LC1K1210P7

TeSys K contactor - 3P - AC-3  $\leq$  440 V 12 A - 1  
NO aux. - 230 V AC coil



### Main

|                           |                                 |
|---------------------------|---------------------------------|
| Range                     | TeSys                           |
| Product or component type | Contactor                       |
| Product name              | TeSys K                         |
| Device short name         | LC1K                            |
| Device application        | Control                         |
| Contactor application     | Resistive load<br>Motor control |

### Complementary

|  |  |
|--|--|
| Utilisation category                   | AC-4<br>AC-1<br>AC-3   |
| Poles description                      | 3P   |
| Power pole contact composition         | 3 NO   |
| [Ue] rated operational voltage         | Power circuit: 690 V AC 50/60 Hz<br>Signalling circuit: $\leq$ 690 V AC 50/60 Hz   |
| [Ie] rated operational current         | 20 A (at $\leq$ 50 °C) at $\leq$ 440 V AC AC-1 for power circuit<br>12 A at $\leq$ 440 V AC AC-3 for power circuit<br>16 A (at $\leq$ 70 °C) at 690 V AC AC-1 for power circuit  |
| Control circuit type                   | AC at 50/60 Hz   |
| [Uc] control circuit voltage           | 230 V AC 50/60 Hz  |
| Motor power kW                         | 4 kW at 480 V AC 50/60 Hz AC-3<br>4 kW at 500...600 V AC 50/60 Hz AC-3<br>4 kW at 660...690 V AC 50/60 Hz AC-3<br>2.2 kW at 400 V AC 50/60 Hz AC-4<br>3 kW at 220...230 V AC 50/60 Hz AC-3<br>5.5 kW at 380...415 V AC 50/60 Hz AC-3<br>5.5 kW at 440 V AC 50/60 Hz AC-3 |
| Auxiliary contact composition          | 1 NO   |
| [Uimp] rated impulse withstand voltage | 8 kV   |

|   |  |
|---|--|
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 20 A (at 50 °C) for power circuit<br>10 A (at 50 °C) for signalling circuit  |
| Irms rated making capacity                  | 110 A AC for signalling circuit conforming to IEC 60947<br>144 A AC for power circuit conforming to NF C 63-110<br>144 A AC for power circuit conforming to IEC 60947  |
| Rated breaking capacity                     | 110 A at 440 V conforming to IEC 60947<br>80 A at 500 V conforming to IEC 60947<br>70 A at 660...690 V conforming to IEC 60947   |
| [Icw] rated short-time withstand current    | 115 A 50 °C - 1 s for power circuit<br>105 A 50 °C - 5 s for power circuit<br>100 A 50 °C - 10 s for power circuit<br>75 A 50 °C - 30 s for power circuit<br>55 A 50 °C - 1 min for power circuit<br>50 A 50 °C - 3 min for power circuit<br>80 A - 1 s for signalling circuit<br>90 A - 500 ms for signalling circuit<br>110 A - 100 ms for signalling circuit<br>25 A 50 °C - >= 15 min for power circuit  |
| Associated fuse rating                      | 25 A gG at <= 440 V for power circuit<br>25 A aM for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947<br>10 A gG for signalling circuit conforming to VDE 0660  |
| Average impedance                           | 3 mOhm - Ith 20 A 50 Hz for power circuit  |
| [Ui] rated insulation voltage               | Power circuit: 600 V conforming to UL 508<br>Power circuit: 690 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-5-1<br>Signalling circuit: 600 V conforming to UL 508<br>Power circuit: 600 V conforming to CSA C22.2 No 14<br>Signalling circuit: 600 V conforming to CSA C22.2 No 14   |
| Insulation resistance                       | > 10 MOhm for signalling circuit   |
| Inrush power in VA                          | 30 VA (at 20 °C)   |
| Hold-in power consumption in VA             | 4.5 VA (at 20 °C)  |
| Heat dissipation                            | 1.3 W  |
| Control circuit voltage limits              | Operational: 0.8...1.15 U <sub>c</sub> (at <50 °C)<br>Drop-out: 0.2...0.75 U <sub>c</sub> (at <50 °C)  |
| Connections - terminals                     | Screw clamp terminals 1 cable(s) 1.5...4 mm <sup>2</sup> solid<br>Screw clamp terminals 1 cable(s) 0.75...4 mm <sup>2</sup> flexible without cable end<br>Screw clamp terminals 1 cable(s) 0.34...2.5 mm <sup>2</sup> flexible with cable end<br>Screw clamp terminals 2 cable(s) 1.5...4 mm <sup>2</sup> solid<br>Screw clamp terminals 2 cable(s) 0.75...4 mm <sup>2</sup> flexible without cable end<br>Screw clamp terminals 2 cable(s) 0.34...1.5 mm <sup>2</sup> flexible with cable end |
| Maximum operating rate                      | 3600 cyc/h   |
| Auxiliary contacts type                     | type instantaneous 1 NO  |
| Signalling circuit frequency                | <= 400 Hz  |
| Minimum switching current                   | 5 mA for signalling circuit  |
| Minimum switching voltage                   | 17 V for signalling circuit  |
| Mounting support                            | Plate<br>Rail  |
| Tightening torque                           | 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm  |
| Operating time                              | 10...20 ms coil de-energisation and NO opening<br>10...20 ms coil energisation and NO closing  |
| Safety reliability level                    | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1   |
| Non overlap distance                        | 0.5 mm   |
| Mechanical durability                       | 10 Mcycles   |
| Electrical durability                       | 0.3 Mcycles 20 A AC-1 at U <sub>e</sub> <= 440 V<br>1.3 Mcycles 12 A AC-3 at U <sub>e</sub> <= 440 V   |
| Mechanical robustness                       | Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27<br>Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27<br>Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27<br>Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27  |

Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27  
 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27  
 Vibrations contactor closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6  
 Vibrations contactor opened: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6

|            |         |
|------------|---------|
| Height     | 58 mm   |
| Width      | 45 mm   |
| Depth      | 57 mm   |
| Net weight | 0.18 kg |

## Environment

|                                     |  |
|-------------------------------------|--|
| Standards                           | BS 5424<br>IEC 60947<br>NF C 63-110<br>VDE 0660  |
| Product certifications              | UL<br>CSA  |
| IP degree of protection             | IP2x conforming to VDE 0106  |
| Protective treatment                | TC conforming to IEC 60068<br>TC conforming to DIN 50016   |
| Ambient air temperature for storage | -50...80 °C  |
| Operating altitude                  | 2000 m without   |
| Flame retardance                    | V1 conforming to UL 94<br>Requirement 2 conforming to NF F 16-101<br>Requirement 2 conforming to NF F 16-102 |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)