

Product datasheet

Characteristics

LR2K0307

TeSys K - differential thermal overload relays -
1.2...1.8 A - class 10A



Main

| | |
|-------------------------------------|---|
| Range | TeSys |
| Product name | TeSys LRK |
| Product or component type | Differential thermal overload relay |
| Device short name | LR2K |
| Relay application | Motor protection |
| Product compatibility | LC1K LP1K LP4K LC7K |
| Network type | AC DC |
| Thermal overload class | Class 10A conforming to IEC 60947-4-1 |
| Thermal protection adjustment range | 1.2...1.8 A |
| [Ui] rated insulation voltage | Power circuit: 690 V conforming to BS 4941 Power circuit: 690 V conforming to IEC 60947 Power circuit: 750 V conforming to VDE 0110 group C Power circuit: 600 V conforming to CSA C22.2 No 14 |

Complementary

| | |
|---|---|
| Network frequency | <= 400 Hz |
| Mounting support | Under contactor Plate, with specific accessories Rail, with specific accessories |
| Auxiliary contact composition | 1 NO + 1 NC |
| [Ith] conventional free air thermal current | 6 A for signalling circuit |
| [Ue] rated operational voltage | <= 690 V for power circuit 690 V AC AC-15 for signalling circuit 250 V DC DC-13 for signalling circuit |
| Associated fuse rating | 6 A gG for signalling circuit conforming to VDE 0660 6 A gG for signalling circuit conforming to IEC 60947 |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Power dissipation per pole | 2 W |
| Phase failure sensitivity | Yes conforming to IEC 60947-4-1 |

| | |
|-------------------------|--|
| Local signalling | Trip indicator (yellow) |
| Control type | Red push-button: trip test function Blue push-button: stop and manual reset selector switch: manual or automatic reset |
| Connections - terminals | Screw clamp terminals 1 cable(s) 1.5...4 mm ² solid Screw clamp terminals 2 cable(s) 1.5...4 mm ² solid Screw clamp terminals 1 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 0.75...4 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 0.34...2.5 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 0.34...1.5 mm ² flexible with cable end |
| Tightening torque | 1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm |
| Height | 58 mm |
| Width | 45 mm |
| Depth | 65 mm |
| Net weight | 0.145 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947 NF C 63-650 VDE 0660 BS 4941 |
| Product certifications | UL CSA |
| Protective treatment | TC conforming to IEC 60068 TC conforming to DIN 50016 |
| IP degree of protection | IP2x conforming to IEC 60529 |
| Ambient air temperature for operation | -20...55 °C without derating conforming to IEC 60947 -30...60 °C with derating conforming to IEC 60947 |
| Ambient air temperature for storage | -40...70 °C |
| Operating altitude | 2000 m without derating |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame retardance | V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102 |
| Mechanical robustness | Shocks NO contact: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks NC contact: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations NO contact: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations NC contact: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 |

Offer Sustainability

| | |
|----------------------------|---|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk