DOWNLOADED FROM WWW.SCATTS.CO.UK

PF 22.000 | PFA 20.000
ECOOL FILTERFAN | EXHAUST FILTER 56–67 m³/h

- installation size 2, air flow rate up to 67 m³/h
- system of protection IP 54 and IP 55, NEMA type 12
- UL, cUL approval
- UV-resistance (IP 55 version)
- cut-out compatible with installation size 2 from the 3rd Generation

PRODUCT		PF 22.000					
ARTICLE NO.	IP 54	11622101055	11622151055	11622851055	11622801055	11622701055	Unit
ARTICLE NO.	IP 55	11622103055	11622153055	11622853055	11622803055	11622703055	
DATA							
Rated voltage ±10 %		AC 50 | 60 Hz		DC			
		230	115	12	24	48	V
Unimpeded airflow	IP 54	61 | 67					m³/h
	IP 55	56 | 64					
Airflow rate in comb. with exhaust filter	IP 54	44 | 50					
	IP 55	40 | 46					
Power consumption		19 | 18	20 | 20	5			W
Current consumption		0.12 | 0.18	0.24 | 0.23	0.42	0.21	0.1	A
Noise level according to EN ISO 3741		44 | 44		44			dB (A)
Weight		0.7		0.44			kg
Type of connection		terminal strip		cable, 2-core, length 310 mm			
Fuse		6					A
System of protection according to EN 60529 / UL 50	IP 54	NEMA type 12 - standard filter					
	IP 55	NEMA type 12 - fluted filter					
Filtration efficiency according to EN 779	IP 54	> 90					%
	IP 55	> 90					%
Filter mat quality class according to EN 779	IP 54	G 4					
	IP 55	G 4					
Duty cycle		100					%
Bearing type		sleeve bearing		ball bearing			
Service life L_{10} (+ 40 °C)[1]		37500	40000	62500			h
Temperature range		–40 … +55 | –40 … +131					°C | °F
Design (housing and protection against accidental contact)	IP 54	made of injection-moulded thermoplastic, self-extinguishing, UL 94 V0					
	IP 55	additional: UV-resistant					
Colour		RAL 7035 | different colours available on request					

ACCESSORIES		ARTICLE NUMBER
Exhaust filter	gray	11720001055
Exhaust filter	black	11720001050
Spare filter mats	5 pieces	18611600030
Thermostat		17121000000
Hygrostat		17207000000
Rainhood in stainless steel		18102000014

For additional models, options and voltages visit www.pfannenberg.com or contact us directly.

[1] fan failure is defined as being when the current and speed deviate or the operating noises are out of the ordinary

DOWNLOADED FROM WWW.SCATTS.CO.UK

DOWNLOADED FROM WWW.SCATTS.CO.UK

Cooling capacity performance curves

Static pressure performance curve

PF 22.000 IP 54





PF 22.000 IP 55





Dimensions

mm	PF 22.000		PFA 20.000
	AC	DC	
X	145	145	145
Y	145	145	145
Z1	5	5	5
Z2	70	64	26
A[1]	125	125	125
B[1]	125	125	125

[1] for material thicknesses up to 2 mm
+ 1 mm for thickness of material > 2 mm ≤ 3 mm



DOWNLOADED FROM WWW.SCATTS.CO.UK

SCATTERGOOD & JOHNSON LTD
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS
Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk