

1313852	DATA SHEET	
valid from: 01.01.2019	ÖLFLEX® CLASSIC 400 CP	

Application

ÖLFLEX® CLASSIC 400 CP cables are oil resistant connection and control cables with a Polyurethan outer sheath, for flexible use and fixed installation for medium mechanical abuse. They are also suitable for use in dry, damp or wet areas. They are suitable for outdoor use if the indicated temperature range is observed.

ÖLFLEX® CLASSIC 400 CP cables are increased resistant to oils and at room temperature largely resistant to acids and alkalis. The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted. The screening braid protects against interference from electrical fields.

Application range:

Industrial machinery, machine tools, measurement-, control-, electrical applications, food production and packaging machinery.

Design

Design	based on EN 50525-2-51 resp. VDE 0285-525-2-51 EN 50525-2-21 resp. VDE 0285-525-2-21
Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. VDE 0295, Class 5
Insulation	LAPP special PVC compound P8/1, better than the PVC compound TI2, acc. to EN 50363-3 resp. VDE 0207-363-3
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with whit numbers acc. to DIN EN 50334 resp. VDE 0293-334
Inner sheath	PVC compound TM2 acc. to EN 50363-4-1 resp. VDE 0207-363-4-1
Screen	braid of tinned copper, coverage = 85 % (nominal value)
Outer sheath	Polyurethane compound TMPU acc. to EN 50363-10-2 resp. VDE 0207-363-10-2 colour: silver grey, similar RAL 7001

Electrical properties at 20°C

Specific volume resistivity	> 20 GΩ x cm
Transfer impedance	max. 250 mΩ/m (at 30 MHz)
Rated voltage	U _o / U: 300 / 500 V
Test voltage	Core/Core: 4000 V AC Core/Screen: 4000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 12,5 x cable diameter fixed installation: 4 x cable diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temp. fixed installation: - 40 °C up to +80 °C max. conductor temp.
UV resistance	acc. to EN 50618 resp. VDE 0283-618 acc. to EN 50620 resp. VDE 0285-620 acc. to EN ISO 4892-2-2013, method A (change of colour allowed)
Ozone resistance	acc. to EN 50396 resp. VDE 0473-396, method B
Oil resistance	acc. to EN 50363-10-2 resp. VDE 0207-363-10-2
Tests	acc. to IEC 60811, EN 50395, EN 50396
General requirements	These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)

Creator: LABU / PDC	Document: DB1313852EN	Page 1 of 1
Released: ALTE / PDC	Version: 06	

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk