

# EAO – Your Expert Partner for Human Machine Interfaces

## 10-2512.1142 - Single-LED

### 10-2512.1142 - Single-LED



*Attention: The preview is based on a sample product. This can differ from your current configuration.*

#### Other Attributes

Weight	0,002 kg
Operation current	15 mA $\pm$ 15 %
Operating voltage	24 V AC/DC +10 %

#### Illumination

Socket	BA9s
LED colour	red


#### Optics

Lumi. intensity	350 mcd
Dom. wavelength	630 nm

# EAO – Your Expert Partner for Human Machine Interfaces

10-2512.1142 - Single-LED

## Dimensions



## Additional information

The max. overall length of the lamp may not exceed 25mm

Electrical and optical data are measured at 25 °C

The specified 12, 24, 28, 48 VAC/DC versions are built with a bridge rectifier

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)