



Pushing Performance

## Han 16B Base Surface LC 2 Levers 2 Entri




Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 09 30 016 1270                                                                        |
| Specification      | Han 16B Base Surface LC 2 Levers 2 Entri                                              |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09300161270">https://b2b.harting.com/09300161270</a> |

### Identification

|                          |                         |
|--------------------------|-------------------------|
| Category                 | Hoods/Housings          |
| Series of hoods/housings | Han <sup>®</sup> B      |
| Type of hood/housing     | Surface mounted housing |
| Type                     | Low construction        |

### Version

|                            |                                                   |
|----------------------------|---------------------------------------------------|
| Locking type               | Double locking lever                              |
| Han-Easy Lock <sup>®</sup> | Yes                                               |
| Size                       | 16 B                                              |
| Version                    | Side entry                                        |
| Cable entry                | 2x Pg 21                                          |
| Field of application       | Standard hoods/housings for industrial connectors |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65            |
| Type rating acc. to UL 50 / UL 50E     | 4               |
|                                        | 4X              |
|                                        | 12              |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Aluminium die-cast   |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 7037 (dust grey) |



Pushing Performance

## Material properties

|                                                            |                                       |
|------------------------------------------------------------|---------------------------------------|
| Material (seal)                                            | NBR                                   |
| Material (locking)                                         | Polycarbonate (PC)<br>Stainless steel |
| Colour (locking)                                           | RAL 7037 (dust grey)                  |
| Material flammability class acc. to UL 94 (locking levers) | V-0                                   |
| RoHS                                                       | compliant                             |
| ELV status                                                 | compliant                             |
| China RoHS                                                 | e                                     |
| REACH Annex XVII substances                                | No                                    |
| REACH ANNEX XIV substances                                 | No                                    |
| REACH SVHC substances                                      | No                                    |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| Approvals | DNV GL                                                     |
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                                                        |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 266.4 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)