



Pushing Performance

## Han-Eco Mod.16-HSE-M40



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 41 016 0523  |
| Specification      | Han-Eco Mod.16-HSE-M40  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19410160523">https://b2b.harting.com/19410160523</a> |

### Identification

|                          |                  |
|--------------------------|------------------|
| Category                 | Hoods/Housings   |
| Series of hoods/housings | Han-Eco® Modular |
| Type of hood/housing     | Hood             |

### Version

|              |                      |
|--------------|----------------------|
| Locking type | Double locking lever |
| Size         | 16 B                 |
| Version      | Side entry           |
| Cable entry  | 1x M40               |

### Technical characteristics

|  |                 |
|--|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP65            |

### Material properties

|   |  |
|---|--|
| Material (hood/housing)                   | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)                     | RAL 9005 (jet black)                     |
| Material flammability class acc. to UL 94 | V-0                                      |
| RoHS                                      | compliant                                |
| ELV status                                | compliant                                |
| China RoHS                                | e  |



Pushing Performance

## Material properties

|                             |    |
|-----------------------------|----|
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances  | No |
| REACH SVHC substances       | No |

## Specifications and approvals

|                |                                   |
|----------------|-----------------------------------|
| Specifications | IEC 61984                         |
|                | EN 45545-2 R22: HL1, HL2, HL3     |
|                | EN 45545-2 R23: HL1, HL2, HL3     |
|                | EN 45545-2 R24: HL1, HL2, HL3     |
| UL / CSA       | UL 1977 ECBT2.E235076             |
|                | CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE             | Yes                               |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1  |
| Net weight                     | 159.6 g                                  |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)