



preLink® System



General information

Mating Face	RJ45 acc. to IEC 60603-7, M12 D-coded acc. to IEC 61076-2-101 or M12 X-coded acc. to IEC 61076-2-109		
Number of contacts	8		
Transmission performance	RJ45/ M12 X-coded	M12 D-coded	
	acc. to ISO 11801 category 6 / class E _x up to 500 MHz		
	acc. to ISO 11801 category 5 / class D up to 100 MHz		
Transmission rate	10/100 Mbit/s 1/2,5/5/10 Gbit/s		
Shielding	10/100Mbits		
Termination technology	Fully shielded, 360° shielding contact		
Power over Ethernet	preLink® IDC termination acc. to IEC 60352-4		
Cable diameter	usable for PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at)		
Conductor cross section (solid and stranded)	see table preLink® types	see table preLink® types	see table preLink® types
Current	1,18A at 20°C (see derating diagram)		
Operating voltage	max. 57V DC		
Contact resistance	≤ 20mΩ		
Insulating resistance between contacts	≥ 500MΩ		
Electric strength contact - contact	RJ45/ M12 D-coded 1,0kV	M12 X-coded 0,5kV	
Electric strength contact - shielding	RJ45/ M12 D-coded 1,5kV	M12 X-coded 0,5kV	
Degree of protection	see table preLink® types		
Temperature range	-40°C ... +70°C		
Mating cycles	RJ45 termination	M12 termination	preLink termination
	min. 750	min. 100	min. 10
UL file	pending		
RoHS - compliant	Yes		

* For high flexible wires (for example AWG 22/19) or special wire isolation materials an evaluation test for the IDC connection is recommended.


Material	
Housing material	see table preLink® types
Contact plating	
Plating contact zone	1,27µm (50µinch) Au over Ni

Derating diagram acc. to IEC 60512-5 (current carrying capacity)


The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals.

The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60512-5



Wire map



preLink® types

p/n	type	cable diameter	material	degree protection
20 82 500 0001	preLink® RJ45 Keystone jack w/o preLink block	5 ... 9 mm	zinc die-cast	IP20
20 82 500 0002	preLink® RJ45 Keystone jack angled w/o preLink block	5 ... 9 mm	zinc die-cast	IP20
20 82 501 0001	preLink® RJ45 Keystone jack AWG 24-22	5 ... 9 mm	zinc die-cast	IP20
20 82 001 0001	preLink® RJ45 HIFF jack AWG 24-22	5 ... 9 mm	zinc die-cast	IP20
20 82 001 0002	preLink® RJ45 HIFF jack AWG 27-26	5 ... 9 mm	zinc die-cast	IP20
20 82 000 0002	preLink® RJ45 HIFF jack w/o preLink block	5 ... 9 mm	zinc die-cast	IP20
20 82 101 0001	preLink® extender	5 ... 9 mm	zinc die-cast	IP20
20 82 101 0010	preLink® RJ45 plug w/o preLink block	5 ... 9 mm	zinc die-cast	IP20
20 82 002 0001	Han® 3 A preLink® RJ45 plug insert	5 ... 9 mm	plastic	IP 65/67
20 82 204 0001	Han® PushPull RJ45 plug plastic	6.3 ... 8.8 mm	plastic	IP 65/67
20 82 104 0001	Han® PushPull RJ45 plug metal	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 104 0045	Han® PushPull RJ45 plug metal 45°	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 005 0001	preLink® M12 connector D-coding, 4 poles	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 005 1214	preLink® connector insert, male, M12 D-coding, 4 poles			
20 82 005 0002	preLink® M12 connector X-coding, 8 poles	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 006 1218	preLink® connector insert, male, M12 X-coding, 8 poles			
20 82 000 1210	preLink® M12 housing, empty	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 005 2001	preLink® M12 cable jack D-coding, 4 poles	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 006 2001	preLink® M12 cable jack X-coding, 8 poles	5 ... 9.5 mm	zinc die-cast	IP 65/67
20 82 007 1100	preLink® PCB jack, THR, 8 poles	5 ... 9.5 mm	plastic/metal shielding	IP20

	All Dimensions in mm Original Size DIN A3	Scale 1:1	Free size tol.	Ref. Sub.
	All rights reserved Department EL PD	Created by BALSAN	Inspected by PRIESTER	Standardisation HOFFMANN
		Date 2019-03-14	State Final Release	
Title preLink System				Doc-Key / ECM-Nr. 100571828/UGD/001/F 500000149033
HARTING Electronics GmbH D-32339 Espelkamp		Type DS	Number 20820000000	Rev. F Page 1/1