




**Auxiliary contact, for FAZ, PKNM, 2W, 0.5HP**

**Part no.** FAZ-XAM002  
**Catalog No.** 262414  
**Alternate Catalog No.** FAZ-XAM002  
**EL-Nummer (Norway)** 0001695385

**Delivery program**

Basic function		Accessories for miniature circuit-breaker
Basic function accessories		Auxiliary contacts
Product range		Accessory
Contact sequence		

**Technical data**

**Electrical**

Contact function			2 C/O
Rated operational voltage	$U_e$	V AC	250
Rated frequency	f	Hz	50/60
Rated current	$I_e$	A	4
Conventional free air thermal current	$I_{th}$	A	4
Rated operational current			
AC-15	$I_e$	A	2 (250 V AC)
AC-12	$I_e$	A	3 (250 V AC)
DC-13	$I_e$	A	0.5 (110 V DC)
Rated insulation voltage	$U_i$	V AC	250
Minimum operating voltage per contact	$U_{min}$	V DC	5
Rated impulse withstand voltage	$U_{imp}$	kV	2.5
Rated conditional short-circuit current With 6 A back-up fuse	$I_{sc}$	kA	1
Max. admissible back-up fuse		A gL	
Max. admissible back-up fuse		A gL	4

**Mechanical**

Standard front dimension		mm	45
Enclosure height		mm	80
Mounting width		mm	8.8 (0.5 space unit)
Mounting			On MCB
Degree of protection			
Integrated			IP40
Terminal protection			Protection against electric shock to IEC 536
Terminals			Lift terminals
Terminal capacities		mm <sup>2</sup>	
Solid		mm <sup>2</sup>	0.5 ... 2.5
flexible		mm <sup>2</sup>	0.5 ... 2.5
Tightening torque of terminal screws		Nm	0.8 ... 1.0

**Design verification as per IEC/EN 61439**

Technical data for design verification		
Operating ambient temperature min.	°C	-5
Operating ambient temperature max.	°C	40


**Technical data ETIM 7.0**

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ec1@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Earth leakage circuit breaker and miniature circuit breaker (MCB)
Additional equipment		Other
Attached at delivery		No
Assembly width (TE)		0.5
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		2
Number of fault-signal switches		0
Rated switch current	A	3
Rated voltage	V	250
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		2
Suitable for max. current main contact unit	A	0

**Approvals**

Product Standards		IEC/EN 60947-2; IEC/EN 60898; UL 1077; CSA-C22.2 No. 235; CE marking
UL File No.		E177451
UL Category Control No.		QVNU2, QVNU8
CSA File No.		-
CSA Class No.		3215-30
North America Certification		UL recognized, certified by UL for use in Canada
Degree of Protection		IEC: IP20; UL/CSA Type: -

Dimensions





**SCATTERGOOD  
& JOHNSON LTD**  
ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

**[www.scatts.co.uk](http://www.scatts.co.uk)**