

**DATASHEET - EASY512-DC-TCX****Control relay, 24 V DC, 8DI(2AI), 4DO-Trans, time****Part no. EASY512-DC-TCX****Catalog No. 274112****EL-Nummer (Norway) 4519761**

Powering Business Worldwide™

**Delivery program**

|                                |  |        |  |
|--------------------------------|--|--------|--|
| Basic function                 |  |        | easy500  |
| Description                    |  |        | Stand alone<br>customized laser inscription or delivery with user program possible with EASY-COMBINATION-* product (article No. 2010781) |
| <b>Inputs</b>                  |  |        |  |
| Digital                        |  |        | 8  |
| of which can be used as analog |  |        | 2  |
| <b>Outputs</b>                 |  |        |  |
| Quantity of outputs            |  |        | Transistor: 4  |
| Outputs                        |  | Number | 4  |
| Transistor                     |  |        | 4  |
| <b>Additional features</b>     |  |        |  |
| Real time clock                |  |        | #  |
| Supply voltage                 |  |        | 24 V DC  |
| Software                       |  |        | EASY-SOFT-BASIC/-PRO   |
| Connection type                |  |        | screw terminal   |

**Technical data****General**

|                        |  |    |  |
|------------------------|--|----|--|
| Standards              |  |    | EN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27                                |
| Approvals              |  |    | CSA<br>UL<br>EAC   |
| Dimensions (W x H x D) |  | mm | 71.5 x 90 x 58 (4 PE)  |
| Weight                 |  | kg | 0.2  |
| Mounting               |  |    | Top-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories) |

**Terminal capacities**

|                        |  |                 |                       |
|------------------------|--|-----------------|-----------------------|
| Solid                  |  | mm <sup>2</sup> | 0.2/4 (AWG 22 - 12)   |
| Flexible with ferrule  |  | mm <sup>2</sup> | 0.2/2.5 (AWG 22 - 12) |
| Standard screwdriver   |  | mm              | 0.8 x 3.5             |
| Max. tightening torque |  | Nm              | 0.6                   |

**Climatic environmental conditions**

|                               |   |     |   |
|-------------------------------|---|-----|---|
| Operating ambient temperature |   | °C  | In accordance with IEC 60068-2-1, -25 - +55                 |
| Condensation                  |   |     | Take appropriate measures to prevent condensation           |
| Storage                       | θ | °C  | -40 - +70   |
| relative humidity             |   | %   | in accordance with IEC 60068-2-30, IEC 60068-2-78<br>5 - 95 |
| Air pressure (operation)      |   | hPa | 795 - 1080  |

**Ambient conditions, mechanical**

|  |             |         |  |
|--|-------------|---------|--|
| Protection type (IEC/EN 60529, EN50178, VBG 4)                             |             |         | IP20   |
| Vibrations   |             | Hz      | In accordance with IEC 60068-2-6<br>constant amplitude 0.15 mm: 10 - 57<br>constant acceleration 2 g: 57 - 150 |
| Mechanical shock resistance (IEC/EN 60068-2-27) semi-sinusoidal 15 g/11 ms |             | Impacts | 18   |
| Drop to IEC/EN 60068-2-31  | Drop height | mm      | 50   |
| Free fall, packaged (IEC/EN 60068-2-32)                                    |             | m       | 1  |
| Mounting position  |             |         | Vertical or horizontal   |

**Electromagnetic compatibility (EMC)**


|                                       |  |  |       |
|---------------------------------------|--|--|-------|
| Overvoltage category/pollution degree |  |  | III/2 |
|---------------------------------------|--|--|-------|

|   |     |   |
|---|-----|---|
| Electrostatic discharge (ESD)                                 |     |   |
| applied standard  |     | according to IEC EN 61000-4-2   |
| Air discharge   | kV  | 8   |
| Contact discharge   | kV  | 6   |
| Electromagnetic fields (RFI) to IEC EN 61000-4-3              |     |   |
|   | V/m | 10  |
| Radio interference suppression                                |     |   |
|   |     | EN 55011 Class B, EN 55022 Class B                                    |
| Burst   | kV  | according to IEC/EN 61000-4-4<br>Supply cables: 2<br>Signal cables: 2 |
| power pulses (Surge)  |     | according to IEC/EN 61000-4-5<br>1 kV (supply cables, symmetrical)    |
| Immunity to line-conducted interference to (IEC/EN 61000-4-6) | V   | 10  |

### Insulation resistance

|   |  |                                      |
|---|--|--------------------------------------|
| Clearance in air and creepage distances |  | EN 50178, UL 508, CSA C22.2, No. 142 |
| Insulation resistance                   |  | EN 50178                             |

### Back-up of real-time clock

|                                       |       |                         |  |
|---------------------------------------|-------|-------------------------|--|
| Back-up of real-time clock            |       |                         |                |
|                                       |       |                         | ① Backup time (hours) with fully charged double layer capacitor<br>② Service life (years)        |
| Accuracy of real-time clock to inputs | s/day | typ. ± 2 (± 0.2 h/Year) |  |
|                                       |       |                         | depending on ambient air temperature fluctuations of up to ± 5 s/day (± 0.5 h/year) are possible |

### Repetition accuracy of timing relays

|                                       |     |     |
|---------------------------------------|-----|-----|
| Accuracy of timing relays (of values) | %   | ± 1 |
| Resolution                            |     |     |
| Range "S"                             | ms  | 10  |
| Range "M:S"                           | s   | 1   |
| Range "H:M"                           | min | 1   |

### Retentive memory

|                                      |  |                            |
|--------------------------------------|--|----------------------------|
| Write cycles of the retentive memory |  | 1000000 (10 <sup>6</sup> ) |
|--------------------------------------|--|----------------------------|

### Power supply

|                           |                |    |   |
|---------------------------|----------------|----|---|
| Rated operational voltage | U <sub>e</sub> | V  | 24 DC (-15/+20%)  |
| Permissible range         | U <sub>e</sub> |    | 20.4 - 28.8 V DC  |
| Residual ripple           |                | %  | ≤ 5   |
| Siemens MPI, (optional)   |                |    | yes (Notice: A short-circuit will result if 0 V or earth is applied to the outputs in the event that the supply voltage is connected to the wrong poles.) |
| Input current             |                |    | normally 80 mA at U <sub>e</sub>  |
| Voltage dips              |                | ms | ≤ In accordance with IEC 61131-2<br>≤ 10  |
| Fuse                      |                | A  | ≥ 1A (T)  |
| Power loss                | P              | W  | Normally 2  |

### Digital inputs 24 V DC

|                                     |                |      |  |
|-------------------------------------|----------------|------|--|
| Number                              |                |      | 8  |
| Inputs can be used as analog inputs |                |      | 2 (I7, I8)   |
| Potential isolation                 |                |      | from power supply: no<br>between digital inputs: no<br>from the outputs: yes<br>to interface/memory card: no |
| Rated operational voltage           | U <sub>e</sub> | V DC | 24   |
| Input voltage                       |                | V DC | Signal 0: ≤ 5 (I1 - I8)<br>Signal 1: ≥ 15 (I1 - I6), ≥ 8 (I7, I8)  |
| Input current at signal 1           |                | mA   | I1 - I6: 3.3 (at 24 V DC)<br>I7, I8: 2.2 (at 24 V DC)  |
| Deceleration time                   |                | ms   | 20 (0 -> 1/1 -> 0, Debounce ON)<br>normally 0.25 (0 -> 1, Debounce OFF, I1 - I8)                             |
| Cable length                        |                | m    | 100 (unshielded)   |
| Frequency counter                   |                |      |  |
| Number                              |                |      | 2 (I3, I4)   |
| Counter frequency                   |                | kHz  | ≤ 1  |
| Pulse shape                         |                |      | Square   |

|                      |  |     |                 |
|----------------------|--|-----|-----------------|
| Pulse pause ratio    |  |     | 1:1             |
| Cable length         |  | m   | ≤ 20 (screened) |
| Rapid counter inputs |  |     |                 |
| Number               |  |     | 2 (I1, I2)      |
| Cable length         |  | m   | ≤ 20 (screened) |
| Counter frequency    |  | kHz | ≤ 1             |
| Pulse shape          |  |     | Square          |
| Pulse pause ratio    |  |     | 1:1             |

### Analog inputs

|                                 |  |    |  |
|---------------------------------|--|----|--|
| Number                          |  |    | 2 (I7, I8)   |
| Potential isolation             |  |    | from power supply: no<br>between digital inputs: no<br>from the outputs: yes<br>to interface/memory card: no |
| Input type                      |  |    | DC voltage   |
| Signal range                    |  |    | 0-10 V DC  |
| Resolution                      |  |    | 0.01 V analog<br>0.01 V digital<br>10 Bit (value 0 - 1023)   |
| Input impedance                 |  | kΩ | 11.2   |
| Accuracy of actual value        |  |    |  |
| two devices from series         |  | %  | ± 3  |
| Within a single device          |  | %  | ± 2, (I7, I8, I11, I12) ± 0.12 V   |
| Conversion time, analog/digital |  | ms | Input delay ON: 20; Input delay OFF: each cycle time   |
| Input current                   |  | mA | < 1  |
| Cable length                    |  | m  | ≤ 30, screened   |

### Transistor outputs

|  |       |              |   |
|--|-------|--------------|---|
| Number   |       |              | 4   |
| Rated operational voltage  | $U_e$ | V DC         | 24  |
| Permissible range  | $U_e$ |              | 20.4 - 28.8 V DC  |
| Residual ripple  |       | %            | 5   |
| Supply current   |       | mA           | Norm./max. 9/16 at signal 0<br>12/22 at signal 1  |
| Siemens MPI, (optional)  |       |              | yes (Notice: A short-circuit will result if 0 V or earth is applied to the outputs in the event that the supply voltage is connected to the wrong poles.) |
| Potential isolation  |       |              | from power supply: yes<br>From the inputs: yes<br>to the interface: yes<br>to the memory card: yes  |
| Rated operational current at signal „1“ DC per channel   | $I_e$ | A            | Max. 0.5  |
| Residual current on 0 signal per channel   |       | mA           | < 0.1   |
| Max. output voltage  |       | V            | 2.5 (signal 0 at external load < 10 MΩ)<br>$U = U_e - 1$ V (signal 1 at $I_e = 0.5$ A)  |
| Short-circuit protection   |       |              | Yes, thermal (analysis via diagnostics input I16, I15; R15, R16)  |
| Short-circuit tripping current for $R_a \leq 10$ mΩ  |       | A            | $0.7 \leq I_e \leq 2$ per output  |
| Total short-circuit current  |       | A            | 8   |
| Peak short-circuit current   |       | A            | 16  |
| Thermal cutout   |       |              | Yes   |
| Max. operating frequency with constant resistive load  |       | Operations/h | 40000   |
| Parallel connection of outputs   |       |              |   |
| With resistive load, inductive load with external suppressor circuit, combination within a group |       |              | Group 1: Q1 to Q4   |
| Number of outputs  | max.  |              | 4   |
| Max. total current   |       | A            | 2 (Caution! Outputs must be actuated simultaneously and for the same length of time.)   |
| Output status indication   |       |              | LCD-display   |
| Inductive load to EN 60947-5-1   |       |              |   |
| Without external suppressor circuit  |       |              |   |
| $T_{0.95} = 1$ ms, $R = 48$ Ω, $L = 16$ mH   |       |              |   |
| Utilization factor   |       | g            | 0.25  |

|  |  |           |                                     |
|--|--|-----------|-------------------------------------|
| Duty factor  |  | % DF      | 100                                 |
| Max. switching frequency f = 0.5 Hz (max. DF = 50 %)   |  | Operation | 3500                                |
| DC-13, T <sub>0.95</sub> = 72 ms, R = 48 Ω, L = 1.15 H |  |           |                                     |
| Utilization factor                                     |  | g         | 0.25                                |
| Duty factor  |  | % DF      | 100                                 |
| Max. switching frequency f = 0.5 Hz (max. DF = 50 %)   |  | Operation | 3500                                |
| T <sub>0.95</sub> = 15 ms, R = 48 Ω, L = 0.24 H        |  |           |                                     |
| Utilization factor                                     |  | g         | 0.25                                |
| Duty factor  |  | % DF      | 100                                 |
| Max. switching frequency f = 0.5 Hz (max. DF = 50 %)   |  | Operation | 3500                                |
| With external suppressor circuit                       |  |           |                                     |
| Utilization factor                                     |  | g         | 1                                   |
| Duty factor  |  | % DF      | 100                                 |
| Max. switching frequency, max. duty factor             |  | Operation | Depending on the suppressor circuit |

**Supply voltage U<sub>Aux</sub>**

|                         |   |   |   |
|-------------------------|---|---|---|
| Siemens MPI, (optional) |   |   | yes (Notice: A short-circuit will result if 0 V or earth is applied to the outputs in the event that the supply voltage is connected to the wrong poles.) |
| Power loss              | P | W | 2   |

**Design verification as per IEC/EN 61439**

|  |                   |    |  |
|--|-------------------|----|--|
| Technical data for design verification   |                   |    |  |
| Rated operational current for specified heat dissipation   | I <sub>n</sub>    | A  | 0  |
| Heat dissipation per pole, current-dependent   | P <sub>vid</sub>  | W  | 0  |
| Equipment heat dissipation, current-dependent  | P <sub>vid</sub>  | W  | 0  |
| Static heat dissipation, non-current-dependent   | P <sub>vs</sub>   | W  | 2  |
| Heat dissipation capacity  | P <sub>diss</sub> | W  | 0  |
| Operating ambient temperature min.   |                   | °C | -25  |
| Operating ambient temperature max.   |                   | °C | 55   |
| IEC/EN 61439 design verification   |                   |    |  |
| 10.2 Strength of materials and parts   |                   |    |  |
| 10.2.2 Corrosion resistance  |                   |    | Meets the product standard's requirements.   |
| 10.2.3 Verification of thermal stability of enclosures   |                   |    |  |
| 10.2.3.1 Verification of thermal stability of enclosures   |                   |    | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |                   |    |  |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |                   |    | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    |  |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |                   |    | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |                   |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |                   |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |                   |    | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |                   |    | Meets the product standard's requirements.   |
| 10.4 Clearances and creepage distances   |                   |    | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |                   |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |                   |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  |                   |    | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |                   |    | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |                   |    |  |
| 10.9.2 Power-frequency electric strength   |                   |    | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |                   |    | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |                   |    | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |                   |    | Is the panel builder's responsibility.   |
| 10.12 Electromagnetic compatibility  |                   |    | Is the panel builder's responsibility.   |
| 10.13 Mechanical function  |                   |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0


|  |   |             |
|--|---|-------------|
| PLC's (EG000024) / Logic module (EC001417)   |   |             |
| Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / Logic module (ecl@ss10.0.1-27-24-22-16 [AKE539014]) |   |             |
| Supply voltage AC 50 Hz  | V | 0 - 0       |
| Supply voltage AC 60 Hz  | V | 0 - 0       |
| Supply voltage DC  | V | 20.4 - 28.8 |
| Voltage type of supply voltage   |   | DC          |
| Switching current  | A | 0.5         |
| Number of analogue inputs  |   | 2           |
| Number of analogue outputs   |   | 0           |
| Number of digital inputs   |   | 8           |
| Number of digital outputs  |   | 4           |
| With relay output  |   | No          |
| Number of HW-interfaces industrial Ethernet  |   | 0           |
| Number of interfaces PROFINET  |   | 0           |
| Number of HW-interfaces RS-232   |   | 0           |
| Number of HW-interfaces RS-422   |   | 0           |
| Number of HW-interfaces RS-485   |   | 0           |
| Number of HW-interfaces serial TTY   |   | 0           |
| Number of HW-interfaces USB  |   | 0           |
| Number of HW-interfaces parallel   |   | 0           |
| Number of HW-interfaces Wireless   |   | 0           |
| Number of HW-interfaces other  |   | 1           |
| With optical interface   |   | No          |
| Supporting protocol for TCP/IP   |   | No          |
| Supporting protocol for PROFIBUS   |   | No          |
| Supporting protocol for CAN  |   | No          |
| Supporting protocol for INTERBUS   |   | No          |
| Supporting protocol for ASI  |   | No          |
| Supporting protocol for KNX  |   | No          |
| Supporting protocol for MODBUS   |   | No          |
| Supporting protocol for Data-Highway   |   | No          |
| Supporting protocol for DeviceNet  |   | No          |
| Supporting protocol for SUCONET  |   | No          |
| Supporting protocol for LON  |   | No          |
| Supporting protocol for PROFINET IO  |   | No          |
| Supporting protocol for PROFINET CBA   |   | No          |
| Supporting protocol for SERCOS   |   | No          |
| Supporting protocol for Foundation Fieldbus  |   | No          |
| Supporting protocol for EtherNet/IP  |   | No          |
| Supporting protocol for AS-Interface Safety at Work  |   | No          |
| Supporting protocol for DeviceNet Safety   |   | No          |
| Supporting protocol for INTERBUS-Safety  |   | No          |
| Supporting protocol for PROFIsafe  |   | No          |
| Supporting protocol for SafetyBUS p  |   | No          |
| Supporting protocol for other bus systems  |   | No          |
| Radio standard Bluetooth   |   | No          |
| Radio standard WLAN 802.11   |   | No          |
| Radio standard GPRS  |   | No          |
| Radio standard GSM   |   | No          |
| Radio standard UMTS  |   | No          |
| IO link master   |   | No          |
| Redundancy   |   | No          |
| With display   |   | No          |
| Degree of protection (IP)  |   | IP20        |

|                                       |  |    |      |
|---------------------------------------|--|----|------|
| Basic device                          |  |    | Yes  |
| Expandable                            |  |    | No   |
| Expansion device                      |  |    | No   |
| With timer                            |  |    | Yes  |
| Rail mounting possible                |  |    | Yes  |
| Wall mounting/direct mounting         |  |    | Yes  |
| Front build in possible               |  |    | No   |
| Rack-assembly possible                |  |    | No   |
| Suitable for safety functions         |  |    | No   |
| Category according to EN 954-1        |  |    | None |
| SIL according to IEC 61508            |  |    | None |
| Performance level acc. EN ISO 13849-1 |  |    | None |
| Appendant operation agent (Ex ia)     |  |    | No   |
| Appendant operation agent (Ex ib)     |  |    | No   |
| Explosion safety category for gas     |  |    | None |
| Explosion safety category for dust    |  |    | None |
| Width                                 |  | mm | 71.5 |
| Height                                |  | mm | 90   |
| Depth                                 |  | mm | 58   |

## Approvals

|                             |  |  |   |
|-----------------------------|--|--|---|
| Product Standards           |  |  | IEC/EN see Technical Data; UL 508; CSA C22.2 No. 142-M1987; CSA C22.2 No. 213-M1987; CE marking |
| UL File No.                 |  |  | E135462   |
| UL Category Control No.     |  |  | NRAQ  |
| CSA File No.                |  |  | 012528  |
| CSA Class No.               |  |  | 2252-01 + 2258-02   |
| North America Certification |  |  | UL listed, CSA certified  |
| Degree of Protection        |  |  | IEC: IP20, UL/CSA Type: -   |

**Dimensions**





# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)