

DATASHEET - SWD4-5LR5-2S

SmartWire-DT round cable IP67, 5 meters, 5-pole, Prefabricated with M12 plug and M12 socket

Powering Business Worldwide™



Part no. SWD4-5LR5-2S
Catalog No. 174768
Alternate Catalog No. SWD4-5LR5-2S

Similar to illustration

Delivery program

| | | | |
|--|--|---|---|
| Product range | | | SmartWire-DT accessories |
| Basic function | | | SWD round cable |
| Function | | | For connecting peripheral SmartWire-DT cards |
| Description | | | 5 pole prefabricated with M12 socket and M12 plug, A-keyed |
| Length | | m | 5 |
| Note regarding length | | | 1 off |
| Connection to SmartWire-DT | | | yes |
| For use with | | | EU1...-SWD... EU2...-SWD... EU6...-SWD... EU8...-SWD-... |
| Protection type (IEC/EN 60529, EN50178, VBG 4) | | | IP67 |

Technical data

General

| | | | |
|-----------|--|--|-----------|
| Approvals | | | UL CSA |
|-----------|--|--|-----------|

Ambient conditions, mechanical

| | | | |
|--|--|--|------|
| Protection type (IEC/EN 60529, EN50178, VBG 4) | | | IP67 |
|--|--|--|------|

Climatic environmental conditions

| | | | |
|---|--|----|-------------|
| Operating ambient temperature (IEC 60068-2) | | °C | |
| Operating ambient temperature max. | | °C | + 70 |
| Condensation | | | permissible |

Design verification as per IEC/EN 61439

| | | | |
|--|------------|----|--|
| Technical data for design verification | | | |
| Static heat dissipation, non-current-dependent | P_{vs} | W | 0 |
| Heat dissipation capacity | P_{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |
| Degree of Protection | | | IP67 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Meets the product standard's requirements. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |

| | | |
|--|--|--|
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 7.0

| | | |
|--|-----------------|---------------------------------|
| Cables (EG000001) / Data and communication cable (copper) (EC003249) | | |
| Conductor surface | | Bare |
| Diameter conductor | mm | 1.5 |
| Nominal cross section conductor | mm ² | 0.5 |
| AWG-size | | 20 |
| Conductor category | | Class 2 = stranded |
| Number of cores | | 5 |
| Number of stranding elements | | 5 |
| Stranding element | | Pairs |
| Core insulation material | | |
| Specification core insulation | | Other |
| Core identification | | Colour |
| Screen over stranding element | | Foil |
| Stranding | | Bundle |
| Screen over stranding | | None |
| Longitudinal water blocking cable | | Yes |
| Radial water blocking cable | | Yes |
| Protective sheath | | |
| Armouring | | No |
| Material outer sheath | | Polyvinyl chloride (PVC) |
| Specification material outer sheath | | Polypropylene |
| Colour outer sheath | | Green |
| Reaction-to-fire class according to EN 13501-6 | | None |
| Smoke development class according to EN 13501-6 | | None |
| Euro class flaming droplets/particles according to EN 13501-6 | | None |
| Euro class acidity according to EN 13501-6 | | None |
| Halogen free (acc. EN 60754-1/2) | | No |
| Halogen free (acc. IEC 60754-2) | | No |
| Flame retardant | | In accordance with EN 60332-1-2 |
| Low smoke (acc. EN 61034-2) | | No |
| Low smoke (acc. IEC 61034-2) | | No |
| Oil resistant (acc. EN 60811-404) | | Yes |
| Oil resistant (acc. IEC 60811-404) | | Yes |
| Insulation integrity in accordance with IEC 60331 | | No |
| Circuit integrity | | No |
| Outer diameter approx. | mm | 5.6 |
| Min. permitted bending radius, moving application with forced guidance | mm | 46 |
| Min. permitted bending radius, moving application/free movement | mm | 46 |
| Min. permitted bending radius, stationary application/permanent installation | mm | 34 |
| Permitted cable outer temperature during assembling/handling | °C | -40 - 80 |
| Permitted cable outer temperature after assembling without vibration | °C | -40 - 80 |
| Category | | Other |

| | | | |
|--------------------------|--|---|------|
| NVP value | | % | 66.5 |
| Underground installation | | | No |
| UV resistant | | | Yes |

Approvals

| | | | |
|--------------------------------------|--|--|--------------------------|
| UL File No. | | | E149111 |
| North America Certification | | | UL listed, CSA certified |
| Specially designed for North America | | | No |

Dimensions





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk