

Design:

2-way solenoid valve, direct acting, normally closed (Circuit function A).

Seal Materials and Fluids handled:

See Table 1.

Fluid and Ambient Temperature:

For Hazardous Locations Div. 1 (T4 rated)

Max. Ambient Temperature 104 °F (40 °C)
 Max. Fluid Temperature 194 °F (90 °C)

The UL-listed valve for Hazardous Locations is suitable for the fluids air, inert gas, water and gasoline.

For Hazardous Locations Div. 1 (T6 rated)

Max. Ambient Temperature 104 °F (40 °C)
 Max. Fluid Temperature 140 °F (60 °C)

For Intrinsically Safe Apparatus for use in Class I, II and III, Division 1 Hazardous Locations (T6 rated)

Max. Ambient Temperature 140 °F (60 °C)
 Max. Fluid Temperature 140 °F (60 °C)

For Hazardous Locations Div. 2 and Ordinary Locations:

See Table 1.

Pressure Range:

Maximum inlet pressure see label on valve.

Installation:


Before installing valve ensure that piping etc. is free of foreign matter (metal shavings, pipe sealing materials, welding scale etc.). Installation as required but preferable with coil uppermost. Installation in this position tends to prevent foreign matter remaining in core tube (increased life). Do not put any loads on coil unit.

PTFE tape is recommended for sealing ports. The arrow on the valvebody indicates the direction of flow.

Assembly instructions:

The conduit connector on the coil (4) must be supported against torque during the assembly using appropriate tools (1) (i.e. pliers, gripper...) (for example a gripper).

While tightening for example a fitting (3) into the conduit connector attention must be paid to the fact that a max. torque of 20Nm (177lbf in) is not exceeded.



Marking (example):

Body Material


BR = Brass
 SS = Stainless Steel

Seal Material

EPDM
 NBR
 FKM

Circuit function

A = Normally Closed
 B = Normally Open



Item No. _____

Voltage / Frequency / Power Consumption _____

Maximum Pressure _____

Approvals

The valve is either approved as

- General Purpose valve for Hazardous Locations
- Class I, Division 1, Group A, B, C, D
- Class II, Division 1, Group E, F, G
- Class III, Division 1 and 2
- Operating Temperature T 4

or

- General Purpose valve for Hazardous Locations
- Class I, Division 1, Group A, B, C, D
- Class II, Division 1, Group E, F, G
- Class III, Division 1 and 2
- Operating Temperature T 6

or

- Intrinsically Safe Apparatus for Hazardous Locations
- Class I, Division 1, Group A, B, C, D
- Class II, Division 1, Group E, F, G
- Class III, Division 1
- Operating Temperature T 6

or


- FM approved as
- Nonincendive for Hazardous Locations
- Class I, Division 2, Group A, B, C, D
- Class II, Division 2, Group F, G
- Class III, Division 1 and 2
- Operating Temperature T 4
- UL listed for General Purpose
- CSA approved for General Purpose

See label on the valve.

Operating Instructions 1810/13_EN-EN_00801551

MAN 1000010154 EN Version: Q Status: RL (released | freigegeben) printed: 22.10.2018

Valve Series	Fluid Temperature		Ambient Temperature		Fluids
	[°F]	[°C]	[°F]	[°C]	
Non-hazardous Fluid					
EPDM	-13 to 194	-25 to 90	-13 to 131	-25 to 55	dry air, inert gas
	41 to 194	5 to 90	41 to 131	5 to 55	water
NBR	32 to 176	0 to 80	32 to 131	0 to 55	dry air, inert gas
	41 to 176	5 to 80	41 to 131	5 to 55	water
FKM	32 to 194	0 to 90	32 to 131	0 to 55	dry air, inert gas
	41 to 194	5 to 90	41 to 131	5 to 55	water
Hazardous Fluid					
FKM	32 to 194	0 to 90	32 to 131	0 to 55	oil, LP gas, oxygen

Wiring Diagram**Electrical Connection Type 2509**

* Orientation is not important

Electrical Connection:

Ensure supply voltage/frequency corresponds with that on label.

Voltage tolerance is $\pm 10\%$.

Available Electrical Connections see "Marking".

Wiring diagram see above.

For this product to be considered UL-listed and CSA approved for General Purpose and FM approved for Hazardous Locations Division 2, it must be in conjunction with the type 2509 cable plug connector (Electrically Operated Valves Parts, YSY12).

The connector and gasket must be assembled to the valve with the screw provided after the connection of the wire leads. This valve and connector assembly is delivered together and is to be used as one unit.

For valves to be used in Intrinsically Safe Applications the positive pole is identified by a "+" on the pin or wire No. 1 has to be connected to the "+".

See Control Drawing for the Rules of Interconnection.

Warning:

All valves to be used in Intrinsically Safe Applications must be clearly marked as Intrinsically Safe Apparatus.

Trouble-Shooting:

Check port connections, minimum operating pressure differential if required and supply voltage. Ensure pilot hole in piston is clear and pilot bore in the valve outlet is not obstructed. If core does not pull in, check for short circuit, coil burn-out or foreign matter impeding core movement. A jammed or missing core causes the coil to overheat in the case of AC supply.

Warning:

These products are designed to operate in a wide variety of applications, it is the user's responsibility to select a model that is appropriate for the application. This product is designed to be installed only by suitably qualified and trained personnel. Specifications should not be exceeded under any circumstances.

The torque for the terminal screw on type 2509 is 0,5 Nm (4,4 lbf-in.).

Changes made to this product will render any applicable warranty null and void.

Specifications subject to change without notice.

Any questions? Please call Bürkert Contromatic Technical Service at (949) 223 31 00.

Germany

Contact address:

Bürkert Fluid Control Systems
Sales Center
Chr.-Bürkert-Str. 13-17
D-74653 Ingelfingen
Tel. + 49 (0) 7940 - 10 91 111
Fax + 49 (0) 7940 - 10 91 448
E-mail: info@de.buerkert.com

International

Contact addresses can be found on the Internet at:

www.burkert.com → Bürkert → Company → Locations



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk