

Design:

2-way solenoid valve, direct acting.

Seal Materials and Fluids handled:

See Table 1.

Fluid and Ambient Temperature:

For Hazardous Locations Div. 1 (T4 rated)

Max. Ambient Temperature 104 °F (40 °C)
 Max. Fluid Temperature 194 °F (90 °C)

The UL-listed valve for Hazardous Locations is suitable for the fluids air, inert gas, water and gasoline.

For Hazardous Locations Div. 1 (T6 rated)

Max. Ambient Temperature 104 °F (40 °C)
 Max. Fluid Temperature 140 °F (60 °C)

For Intrinsically Safe Apparatus for use in Class I, II and III, Division 1 Hazardous Locations (T6 rated)

Max. Ambient Temperature 140 °F (60 °C)
 Max. Fluid Temperature 140 °F (60 °C)

For Hazardous Locations Div. 2 and Ordinary Locations:

See Table 1.

Pressure Range:

Maximum inlet pressure see label on valve.

Installation:

Before installing valve ensure that piping etc. is free of foreign matter (metal shavings, pipe sealing materials, welding scale etc.). Installation as required but preferable with coil uppermost. Installation in this position tends to prevent foreign matter remaining in core tube (increased life). Do not put any loads on coil unit.

PTFE tape is recommended for sealing ports. Mounting is accomplished by means of four M4 x 8 mm tapped holes located on the valve underside. Letters on valve body indicate pressure port, exhaust and outlet of the valve.

Marking (example):

Body Material


BR = Brass
 SS = Stainless Steel

Seal Material

EPDM = EPDM
 NBR = NBR
 FKM = FKM

Circuit function

A = Normally closed
 B = Normally opened



Approvals

The valve is either approved as

General Purpose valve for Hazardous Locations
 Class I, Division 1, Group A, B, C, D
 Class II, Division 1, Group E, F, G
 Class III, Division 1 and 2
 Operating Temperature T 4

or
 General Purpose valve for Hazardous Locations
 Class I, Division 1, Group A, B, C, D
 Class II, Division 1, Group E, F, G
 Class III, Division 1 and 2
 Operating Temperature T 6

or
 Intrinsically Safe Apparatus for Hazardous Locations
 Class I, Division 1, Group A, B, C, D
 Class II, Division 1, Group E, F, G
 Class III, Division 1
 Operating Temperature T 6


or
 FM approved as
 Nonincendive for Hazardous Locations
 Class I, Division 2, Group A, B, C, D
 Class II, Division 2, Group F, G
 Class III, Division 1 and 2
 Operating Temperature T 4
 UL listed for General Purpose
 CSA approved for General Purpose

See label on the valve.

MAN 1000010163 EN Version: L Status: RL (released | freigegeben) printed: 22.09.2017

Operating Instructions 1702/10_EN-EN_00893618

	Seal Designation	Seal Material	Fluid Temperature		Ambient Temperature		Fluids
			[°F]	[°C]	[°F]	[°C]	
Non-hazardous fluids	FF (IB46)	Low Temp. FKM	-40...+212 °F	-40...+100 °C	-40...+131 °F	-40...+55 °C	Air, inert gas
	FF	FKM	+14...+212 °F	-10...+100 °C	+14...+131 °F	-10...+55 °C	Air, inert gas
			+32...+212 °F	0...+100 °C	+32...+131 °F	0...+55 °C	Water
	AA	EPDM	-22...+212 °F	-30...+100 °C	-22...+131 °F	-30...+55 °C	Air, Inert Gas, Steam
			+32...+212 °F	0...+100 °C	+32...+131 °F	0...+55 °C	Water
	EG, EF	PTFE + Graphite, PTFE + FKM	-40...+266 °F	-40...+130 °C	-40...+131 °F	-40...+55 °C	Air, Inert Gas, Steam
+32...+212 °F			0...+100 °C	+32...+131 °F	0...+55 °C	Water	
BB	NBR	+14...+194 °F	-10... +90 °C	+14...+131 °F	-10...+55 °C	Air, Inert Gas, Steam	
		+32...+194 °F	0... +90 °C	+32...+131 °F	0...+55 °C	Water	
Hazardous fluids	BB	NBR	+14...+194 °F	-10... +90 °C	+14...+131 °F	-10...+55 °C	No.2 Fuel Oil
	FF	FKM	+14...+248 °F	-10...+120 °C	+14...+131 °F	-10...+55 °C	

Wiring Diagram**Electrical Connection Type 2509**

* Orientation is not important

Electrical Connection:

Ensure supply voltage/frequency corresponds with that on label.

Voltage tolerance is $\pm 10\%$.

Available Electrical Connections see "Marking".

Wiring diagram see above.

For this product to be considered UL-listed and CSA approved for General Purpose and FM approved for Hazardous Locations Division 2, it must be in conjunction with the type 2509 cable plug connector (Electrically Operated Valves Parts, YSY12).

The connector and gasket must be assembled to the valve with the screw provided after the connection of the wire leads. This valve and connector assembly is delivered together and is to be used as one unit.

For valves to be used in Intrinsically Safe Applications the positive pole is identified by a "+" on the pin or wire No. 1 has to be connected to the "+".

See Control Drawing for the Rules of Interconnection.

Warning:

All valves to be used in Intrinsically Safe Applications must be clearly marked as Intrinsically Safe Apparatus.

Trouble-Shooting:

Check port connections, minimum operating pressure differential if required and supply voltage. Ensure pilot hole in piston is clear and pilot bore in the valve outlet is not obstructed. If core does not pull in, check for short circuit, coil burn-out or foreign matter impeding core movement. A jammed or missing core causes the coil to overheat in the case of AC supply.

Warning:

These products are designed to operate in a wide variety of applications, it is the user's responsibility to select a model that is appropriate for the application. This product is designed to be installed only by suitably qualified and trained personnel. Specifications should not be exceeded under any circumstances.

The torque for the terminal screw on type 2509 is 0,5 Nm (4,4 lbf-in.).

Changes made to this product will render any applicable warranty null and void.

Specifications subject to change without notice.

Germany

Contact address:

Bürkert Fluid Control Systems
Sales Center
Chr.-Bürkert-Str. 13-17
D-74653 Ingelfingen
Tel. + 49 (0) 7940 - 10 91 111
Fax + 49 (0) 7940 - 10 91 448
E-mail: info@burkert.com

International

Contact addresses can be found on the Internet at:

www.burkert.com



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk