




---

 PRODUCT-DETAILS

# OT160EV04P

## OT160EV04P SWITCH-DISCONNECTOR




---

**General Information**

Extended Product Type	OT160EV04P
Product ID	1SCA120521R1001
EAN	6417019519814
Catalog Description	OT160EV04P SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-diconnector with black IP65 handle and shaft, terminal bolt kit included

---

**Popular Downloads**

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301031M0220
Mechanical Drawings	1SCC301392F0001 1SCC301201F0001 OT200-250E04.igs

---

**Dimensions**

Product Net Width	150 mm
Product Net Height	180.5 mm
Product Net Depth /	82.5 mm

Length	
Product Net Weight	1.7 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A (1000 V) 200 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 160 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 48 kW (400 ... 415 V) 88 kW (500 V) 112 kW (690 V) 144 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 200 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 160 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 30 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 8 kA
Power Loss	at Rated Operating Conditions per Pole 3.2 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism at the End of the Switch 04 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 15...22 N·m
Mechanical Durability	20000

---

## Environmental

---

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301149D0202

---



---

## Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	1SCC301131D2705
DNV GL Certificate	1SCC301174D0204
Environmental Information	1SCC301149D0202
Instructions and Manuals	1SCC301031M0220
RoHS Information	1SCC301149D0203

---



---

## Container Information

---

Package Level 1 Units	1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	190 mm 7.5 in
Package Level 1 Height	145 mm 5.7 in
Package Level 1 Gross Weight	1.8 kg 4 lb
Package Level 1 EAN	6417019519814

---



---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden)	3170909

---



---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

OT160EV04P





# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)