



 PRODUCT-DETAILS

OT40F3

OT40F3 SWITCH-DISCONNECTOR



General Information

| | |
|-----------------------|--|
| Extended Product Type | OT40F3 |
| Product ID | 1SCA104902R1001 |
| EAN | 6417019390451 |
| Catalog Description | OT40F3 SWITCH-DISCONNECTOR |
| Long Description | 3-pole, front operated, base mounted, DIN-rail mountable switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle and shaft are not included |

Popular Downloads

| | |
|-----------------------------------|--|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals | 1SCC301052M0006 |
| Mechanical Drawings | 1SCC301434F0001 1SCC301433F0001 OT16-40F3.stp OT16-40F3.igs |

Dimensions

| | |
|----------------------------|-------|
| Product Net Width | 35 mm |
| Product Net Height | 68 mm |
| Product Net Depth / Length | 56 mm |

Product Net Weight 0.09 kg

Technical

| | |
|--|---|
| Rated Operational Current AC-21A (I_e) | (380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 23 A (500 V) 23 A (690 V) 12 A |
| Rated Operational Power AC-23A (P_e) | (220 ... 240 V) 5.5 kW (400 ... 415 V) 11 kW (500 V) 11 kW (690 V) 11 kW |
| Conventional Free-air Thermal Current (I_{th}) | q = 40 °C 40 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 40 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 750 V |
| Rated Operational Voltage | Main Circuit 750 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (690 V) 0.71 kA |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 0.5 kA |
| Power Loss | at Rated Operating Conditions per Pole 1.6 W |
| Pollution Degree | 3 |
| Handle Type | Knob Handle and shaft not included |
| Switches Operating Mechanism | Mechanism on Top of the Switch |
| Distance Between Phases | Standard |
| Position of Line Terminals | Top In - Bottom Out Bottom In - Top Out |
| Operating Mode | Front operated |
| Standards | IEC 60947-3 / UL 508 / CSA C22.2 No. 14 |
| Special Functions | No |
| Mounting Type | Base mounting |
| Number of Poles | 3 |
| Cable Cross-Section | Cu 0.75...10 mm ² |
| Degree of Protection | Front IP20 |
| Terminal Type | Screw Terminals |
| Tightening Torque | acc. IEC 60947-1 0.8 N·m |
| Mechanical Durability | 20000 |

Technical UL/CSA

| | |
|----------------------------------|--|
| Maximum Operating Voltage UL/CSA | 600 V |
| Horsepower Rating UL/CSA | (110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (440 ... 480 V AC) Single Phase 10 Hp (550 ... 600 V AC) Single Phase 15 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp |

(550 ... 600 V AC) Three Phase 25 Hp

| | |
|-----------------------------|---------|
| Ampere Rating UL/CSA | 40 A |
| Tightening Torque UL/CSA | 7 in-lb |

Environmental

| | |
|------------------------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | 1SCC301183D0201 |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC301166D2703 |
| Environmental Information | 1SCC301183D0201 |
| Instructions and Manuals | 1SCC301052M0006 |
| RoHS Information | 1SCC301183D0202 |

Container Information

| | |
|-----------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 67 mm |
| Package Level 1 Depth / Length | 79 mm |
| Package Level 1 Height | 46 mm |
| Package Level 1 Gross Weight | 0.1 kg |
| Package Level 1 EAN | 6417019390451 |

Classifications

| | |
|-------------------------------|--|
| Object Classification Code | Q |
| ETIM 5 | EC000216 - Switch disconnecter |
| ETIM 6 | EC000216 - Switch disconnecter |
| ETIM 7 | EC000216 - Switch disconnecter |
| UNSPSC | 39122233 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Sweden) | 3170939 |

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

OT40F3





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk