



 PRODUCT-DETAILS

OT80F4N2

OT80F4N2 SWITCH-DISCONNECTOR



General Information

Extended Product Type	OT80F4N2
Product ID	1SCA105413R1001
EAN	6417019393483
Catalog Description	OT80F4N2 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted, DIN-rail mountable switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle and shaft are not included

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301064M0212
Mechanical Drawings	1SCC301452F0001 1SCC301451F0001 OT63-80F4N2.igs

Dimensions

Product Net Width	70 mm
Product Net Height	91.5 mm
Product Net Depth / Length	72.5 mm
Product Net Weight	0.3 kg

Technical	
Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 80 A (500 V) 80 A (690 V) 80 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 80 A (500 V) 80 A (690 V) 80 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 75 A (500 V) 58 A (690 V) 20 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 22 kW (400 ... 415 V) 37 kW (500 V) 37 kW (690 V) 18.5 kW
Conventional Free-air Thermal Current (I_{th})	$\vartheta = 40\text{ }^\circ\text{C}$ 80 A
Conventional Thermal Current (I_{the})	Fully Enclosed 80 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 2.1 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 1.5 kA
Power Loss	at Rated Operating Conditions per Pole 4.5 W
Pollution Degree	3
Handle Type	Knob Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Special Functions	No
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	Cu 1.5...35 mm ²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 2 N·m
Mechanical Durability	20000

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 10 Hp (440 ... 480 V AC) Single Phase 20 Hp (550 ... 600 V AC) Single Phase 20 Hp (220 ... 240 V AC) Three Phase 20 Hp

	(440 ... 480 V AC) Three Phase 40 Hp (550 ... 600 V AC) Three Phase 40 Hp	
Ampere Rating UL/CSA		80 A
Tightening Torque UL/CSA		18 in-lb

Environmental

RoHS Status	Following EU Directive 2011/65/EU	
Environmental Information	1SCC301183D0201	

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301167D2704	
Environmental Information	1SCC301183D0201	
Instructions and Manuals	1SCC301064M0212	
RoHS Information	1SCC301183D0202	

Container Information

Package Level 1 Units	1 piece	
Package Level 1 Width	84 mm	
Package Level 1 Depth / Length	103 mm	
Package Level 1 Height	82 mm	
Package Level 1 Gross Weight	0.3 kg	
Package Level 1 EAN	6417019393483	

Classifications

Object Classification Code	Q	
ETIM 5	EC000216 - Switch disconnecter	
ETIM 6	EC000216 - Switch disconnecter	
ETIM 7	EC000216 - Switch disconnecter	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
E-Number (Sweden)	3171071	

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

OT80F4N2





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk