




 PRODUCT-DETAILS

PS1-2-0-65

PS1-2-0-65 Busbar



General Information

Extended Product Type	PS1-2-0-65
Product ID	1SAM201906R1102
EAN	4013614400681
Catalog Description	PS1-2-0-65 Busbar
Long Description	PS1-2-0-65 3-phase busbar for 2 MS116 / MS132, Ie=65A

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010

Popular Downloads

Data Sheet, Technical Information	1SBC100192C02--
Instructions and Manuals	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
Dimension Diagram	1SAM200450F0001

Dimensions

Product Net Width	86.5 mm
-------------------	---------

Product Net Height	32.3 mm
Product Net Depth / Length	13 mm
Product Net Weight	0.034 kg

Technical

Rated Operational Voltage	690 V AC 250 V DC
Rated Operational Current (I _e)	65 A
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Short-time Withstand Current (I _{cw})	100 kA
Number of Mountable Devices	2
Number of Lateral Auxiliary Contacts	0
Number of Phases	3
Degree of Protection	IP20
Pollution Degree	3
Connection Type	Fork
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Product Name	Busbar
Suitable For	MS116 MS132
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	3-Phase Busbar

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Ampere Rating UL/CSA	65 A

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -50 ... +80 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

cUL Certificate	1SAA963001-1701
Declaration of Conformity - CE	1SAD938513-0056
GOST Certificate	1SAA937000-2703
Instructions and Manuals	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
RoHS Information	1SAD938511-0056
UL Certificate	1SAA963001-1602

Container Information


Package Level 1 Width	80 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.37 kg
Package Level 1 EAN	4013614488061
Package Level 1 Units	box 10 piece

Classifications

Object Classification Code	W
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC000215 - Phase busbar
ETIM 6	EC000215 - Phase busbar
ETIM 7	EC000215 - Phase busbar
eClass	7.0 27371306
UNSPSC	39121117
IDEA Granular Category Code (IGCC)	4378 >> Phase busbar
E-Number (Sweden)	3111675

Categories

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters Accessories





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk