




 PRODUCT-DETAILS

S1-M3-35

S1-M3-35 Power Infeed Block



General Information

Extended Product Type	S1-M3-35
Product ID	1SAM201913R1103
EAN	4013614400834
Catalog Description	S1-M3-35 Power Infeed Block
Long Description	S1-M3-35 3-phase power infeed block Flat, for MS116 / MS132, 35mm ² , Type E

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85369010

Popular Downloads

Data Sheet, Technical Information	1SBC100192C02--
Instructions and Manuals	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802

Dimensions

Product Net Width	45.5 mm
Product Net Height	45.7 mm

Product Net Depth / Length	35.3 mm
Product Net Weight	0.06 kg

Technical

Terminal Type	Screw Terminals
Rated Operational Voltage	690 V AC 250 V DC
Rated Operational Current (I _e)	100 A
Number of Poles	3
Degree of Protection	IP20
Connecting Capacity Main Circuit	Flexible 1x 10 ... 35 mm ² Rigid 1x 10 ... 35 mm ²
Tightening Torque	Main Circuit 4.5 N·m
Wire Stripping Length	Main Circuit 12 mm
Recommended Screw Driver	Hexgon SW4
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Product Name	Power Infeed Block
Suitable For	MS116 MS132 MO132
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	3-Phase Power Infeed Block
Remarks	UL/CSA Type E/F and IEC

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Ampere Rating UL/CSA	92 A
Connecting Capacity Main Circuit UL/CSA	Flexible 1x 8-2 AWG Stranded 1x 8-2 AWG
Tightening Torque UL/CSA	Main Circuit 40 in·lb

Environmental

Ambient Air Temperature	Operation -25 ... +70 °C Storage -50 ... +80 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

cUL Certificate	1SAA963001-1701
Declaration of Conformity - CE	1SAD938513-0056
GOST Certificate	1SAA937000-2703
Instructions and Manuals	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
RoHS Information	1SAD938511-0056

UL Certificate

1SAA963001-1602

Container Information


Package Level 1 Width	59 mm
Package Level 1 Depth / Length	245 mm
Package Level 1 Height	38 mm
Package Level 1 Gross Weight	0.638 kg
Package Level 1 EAN	4013614488221
Package Level 1 Units	box 10 piece

Classifications

Object Classification Code	X
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC000275 - Rail terminal bar
ETIM 6	EC000275 - Rail terminal bar
ETIM 7	EC000275 - Rail terminal bar
eClass	7.0 27400603
UNSPSC	39121410
IDEA Granular Category Code (IGCC)	4561 >> Power Blocks & Distribution Blocks
E-Number (Sweden)	3112083

Categories

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters Accessories





SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk