


NH busbar mounted fuse base, 250 A (03601)



The picture may show a similar product.

Description

Part No.: 03601

QUADRON® 60Classic

NH busbar mounted fuse base, 250 A

screw, screw-on on bar

size 1 / 1P

particular article

System

100Energy

185mm-System

Product group 10

Subgroup 30

pack size 3

EAN 4021267036010

catalog page 2015 : 3.3

eCl@ss 6.1 27142106

eCl@ss 7.1 27142106

ETIM 4.0 EC000067

ETIM 5.0 EC000067

Approvals

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014

IEC 60269-2:2013

GB/T 13539.2

Approvals

EAC



EAC Type: NH

Technical data

for fuse links size:

NH 1

fuse links acc. to standard:

IEC / HD 60269-2

permitted power dissipation of the fuse-link: 32 W

Details IEC

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014

IEC 60269-2:2013

GB/T 13539.2

Electrical data IEC

Rated current (IEC): 250 A

rated voltage (IEC) AC: 690 V

rated voltage (IEC) DC: 440 V

rated surge voltage U_{imp} : 6 kV

The insulation performance of the article depends on the installation conditions.

short-circuit strength when protected by fuses: 50 kA

power dissipation of the article:

The power dissipation at a typical load of 80 % of the rated current results to 4.7 W.

(The power dissipation for operation with rated current would be 7.3 W.)

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 800 V

max. permitted voltage (IEC) DC: 800 V

1000V DC, air and creepage distances to DIN EN 60664-1, VDE 0110 Part 1 are to be considered for fuse links IEC 60269-2 / DIN VDE 0636-201 size 1 to 32W power dissipation

Mechanical data

W x H x D: 60 x 175 x 110

weight: 46 kg/100

poles: 1-pole

Type of fastening: can be screwed onto drilled busbar, connection screw: screw connection M10, 18 - 22Nm torque

Terminal points

NHUT_SCHRAUBE_M10

Material properties

Main body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free

Contacts: spring-loaded copper contacts, silver plated


Connecting screws: screw M10, galvanized, chromized

Accessories



03502

NH fuse extractor handle
without sleeve
size 000 - 3



03792

shock protection in two parts
for NH fuse-base
size 1
particular article



79449

grip lug cover
for NH fuse-base
NH 1 - 3



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk