


connection set, 4-pole, without cover (01147)



The picture may show a similar product.

Description

Part No.: 01147

CRITO[®] 60Classic

connection set, 4-pole, without cover

95 - 300 mm², AWG 3/0 - 600 MCM

for busbars 20, 25, 30 x 5, 10 and section busbars

System

60Classic

Product group 07

Subgroup 51

pack size 1

EAN 4021267011475

catalog page 2020 : 3.5

eCl@ss 6.1 27141146
 eCl@ss 7.1 27141146
 ETIM 4.0 EC000001
 ETIM 5.0 EC000001

Approvals

Standards

IEC 61439-1:2011
 IEC 60999-1:1999
 IEC 60999-2:2003
 GB/T 7251.1

Approvals

UL, DNV GL, EAC



for UL feeder circuits >250V

type number: M300-L
 EAC Type: TE-4P

UL file: E123577, UL category (for USA): NMTR <http://www.ul.com>
 UL file: E123577, UL category (for Canada): NMTR7 <http://www.ul.com>
 CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2011
 IEC 60999-1:1999
 IEC 60999-2:2003
 GB/T 7251.1

Electrical data IEC

Rated current (IEC): 500 A
 rated voltage (IEC) AC: 690 V

The insulation performance of the article depends on the installation conditions.

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

max. permitted voltage (IEC) AC: 1000 V

max. permitted voltage (IEC) DC: 1500 V

current capacity (IEC) max.: 560 A

rated peak withstand current I_{pk} max.: 50.3 kA

Details UL

Standards

UL 508

for UL feeder circuits >250V

suitable for field-installed conductors

Electrical data UL

rated current (UL): 420 A

rated voltage (UL) AC: 600 V

SCCR unprotected max.: 22 kA

3 cycles (without OPD) @ 600 V AC

SCCR protected max.: 200 kA

SCCR: 100 kA with JDDZ fuse Class L 1200 A / 600 V AC

200 kA with JDDZ fuse Class L 800 A / 600 V AC

200 kA with fuse JDDZ Class J 600 A / 600 V AC

35 kA with any DIVQ/7 circuit breaker 400 A / 600 V AC

65 kA with any DIVQ/7 circuit breaker 400 A / 480 V AC

Mechanical data

W x H x D: 204 x 224 x 115

weight: 210 kg/100

poles: 4-polig

for busbars: 20, 25, 30 x 5, 10 and section busbars

Terminal points

for applications acc. to IEC / EN :

Cu 95 - 300 mm² stranded round cables and stranded sectored cables as well as flexible cables (directly)

Cu 240 - 300 mm² fine stranded flexible cables (directly)

Al 120 - 300 mm² stranded round cables and stranded sectored cables

Al 120 - 240 mm² solid sectored cables

for applications acc. to UL / CSA :

Cu 95 - 300 mm² / AWG 3/0 - MCM 600

Material properties

Main body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200

Cover: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200

Terminals: galvanised steel, chromited screw: hexagon socket screw, galvanised, chromited, thrust piece brass, nickel-plated

Version

Part no. 01 162 for flat conductors 32x20

Accessories



01597

cover cap, 4-pole

228 mm wide

228 x 260 x 90

for busbars: 12, 15, 20, 25, 30 x 5, 10 and section busbars




01417

cover section

top / bottom, slotted, 1.10 m long, for holders 01136 or 01137

3 x 118 x 1100




01555

cover section

top / bottom, 1.10 m long, for holders 01136 or 01137

3 x 109 x 1100



01599

front cover section, for 4-pole systems

front mounted, 1.10 m long, for holder 01137

3 x 250 x 1100



01137

set of holders for cover sections, for 4-pole busbar systems

set consisting of left and right holder, for covers 01599, 01555 and 01417

for busbars: 12, 15, 20, 25, 30 x 5, 10 and section busbars



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk