

D02 fuse link 63 A (01694)



The picture may show a similar product.

Description

Part No.: 01694

D02 fuse link 63 A

copper, with silver plated contacts

E 18

System

Accessories

Product group 22

Subgroup 01

pack size 10

EAN 4021267016944

catalog page 2020 : 7.6

eCl@ss 6.1 27142119
eCl@ss 7.1 27142119
ETIM 4.0 EC001642
ETIM 5.0 EC001642

Approvals

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014
IEC 60269-3:2010 + A1:2013
GB/T 13539.3

Technical data

size: D02 / E 18

Details IEC

Standards

IEC 60269-1:2006 + A1:2009 + A2:2014
IEC 60269-3:2010 + A1:2013
GB/T 13539.3

Electrical data IEC

Rated current (IEC): 63 A
rated voltage (IEC) AC: 400 V

rated voltage (IEC) DC: 250 V

rated short-circuit breaking capacity AC: 50 kA

rated short-circuit breaking capacity DC: 8 kA

power dissipation of the article:

The power dissipation at a typical load of 80 % of the rated current results to 3.5 W.
(The power dissipation for operation with rated current would be 5.5 W.)

Mechanical data

weight: 1.5 kg/100



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk