

insulator (05791)



The picture may show a similar product.

Description

Part No.: 05791

insulator

with female thread at both sides, length across flats 40

M12 x 40

System

Accessories

Product group 06

Subgroup 89

pack size 20

EAN 4021267057916

catalog page 2020 : 7.17

eCl@ss 6.1 27400607
eCl@ss 7.1 27400607
ETIM 4.0 EC001166
ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011
GB/T 7251.1

Approvals

EAC



EAC Type: IS

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2011
GB/T 7251.1

Electrical data IEC

rated voltage (IEC) AC: 2000 V

rated voltage (IEC) DC: 2000 V

short-circuit withstandability: no data

power dissipation of the article:

The power dissipation at a typical load of 80 % of the rated current results to 0 W.
(The power dissipation for operation with rated current would be 0 W.)

Mechanical data

W x H x D: 40 x 40 x 40

weight: 11.8 kg/100

Material properties

Main body: temperature stability 200°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 600,
halogen-free



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk