

holder for cylindrical fuses (31111)



The picture may show a similar product.

Description

Part No.: 31111

AMBUS® Panel

holder for cylindrical fuses

10 x 38 / 1P + N

32 A / 690 V

N on right side

System

DIN rail

Product group 17

Subgroup 06

pack size 6

EAN 4021267311117

Advantages of the product

large clamping range
holder for label

catalog page 2020 : 6.6

eCl@ss 6.1 27142190

eCl@ss 7.1 27142190

ETIM 4.0 EC002705

ETIM 5.0 EC002705

Approvals

Standards

IEC 60947-1:2007 + A1:2010 + A2:2014

IEC 60947-3:2008 + A1:2012 + A2:2015

GB/T 14048.3

Approvals

IEC (CB) , CSA , UL , CCC , EAC



for UL feeder circuits >250V

type number: AES10x38

EAC Type: AES

UL file: E230163, UL category (for USA): IZLT <http://www.ul.com>

UL file: E230163, UL category (for Canada): IZLT7 <http://www.ul.com>

CSA file: 110285, CSA class: 6225-01 <http://directories.csa-international.org>

CCC certificate: 2012010302581751

Technical data

for fuse links size: 10x38

fuse links acc. to standard: IEC / HD 60269-2

permitted power dissipation of the fuse-link: 3 W

Details IEC**Standards**

IEC 60947-1:2007 + A1:2010 + A2:2014

IEC 60947-3:2008 + A1:2012 + A2:2015

GB/T 14048.3

Electrical data IEC

Rated current (IEC): 32 A

rated voltage (IEC) AC: 690 V

rated isolation voltage U_i AC: 800 V

rated surge voltage U_{imp} : 6 kV

Utilisation category AC (IEC 60947-3): AC-22B (400V)

cond. short-circuit current with fuses (AC): 100 kA / 400 V (32A)

100 kA / 500 V (25A)

approved with fuse links of operation class: gG

power dissipation of the article:

The power dissipation at a typical load of 80 % of the rated current results to 0.6 W.

(The power dissipation for operation with rated current would be 0.9 W.)

A fuse-combination unit acc. to IEC 60947-3 can only be operated at a higher voltage than its rated voltage, if it is used as a fuse-disconnector without breaking capacity, up to its max. rated insulation voltage and labelled as such.

for fuse links as per IEC / EN 60269-2 with permitted rated power dissipations

up to max. 3W for gG/gL

up to max. 1.2W for aM

Details UL**Standards**

UL 4248-1

for UL feeder circuits >250V

suitable for field-installed conductors

Electrical data UL

rated current (UL): 30 A
 rated voltage (UL) AC: 600 V
 rated voltage (UL) DC: 600 V
 for wires UL: Cu 75°C

SCCR: 100 kA

Mechanical data

W x H x D: 36 x 81 x 58
 weight: 11.3 kg/100
 poles: 1-pole+N

degree of protection: IP20
 front degree of protection: IP20

Terminal points

for applications acc. to IEC / EN :

1 wire:

Cu 0,75 - 25 mm²

2 wires (of same cross-section):

Cu 0,75 - 10 mm²

flexible cables, directly or with wire-end ferrule

(flexible cables of max. cross-section may not fit when using wire-end ferrule)

Md 2,0 - 2,5 Nm / 18 - 22 lb.in.

for applications acc. to UL / CSA :

only Cu cables acc. to UL 486E

1 wire:

AWG 18 - AWG 8, Class B, Md 2,0 - 2,5 Nm / 18 - 22 lb.in.

AWG 6 - AWG 4, Class C, Md 2,5 - 3,0 Nm / 22 - 26 lb.in.

2 wires (of identical cross-section):

AWG 18 - AWG 8, Class B, Md 2,0 - 2,5 Nm / 18 - 22 lb.in.

AWG 6, Class C, Md 2,0 - 2,5 Nm / 18 - 22 lb.in.

Material properties

Main body:	temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 600, halogen-free
Fuse-carrier:	temperature stability 125°C, self-extinguishing in acc. to UL 94, creepage resistance CTI 600, halogen-free
Connecting screws:	screw +/- (PZ2), galvanized, chromized

Version

Version with indicator light: Part no. 31131

Accessories



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk