



# MICRO SWITCH Limit Switch Comparison

Series	SZL-VL-S	NGC	14CE	914CE	E6/V6	E7/V7	Compact LS	200LS (plug-in)	SZL-WL	GLA	GLC	GLD	GLE	HDLS Std & plug-in	HDLS epoxy sealed body	HDLS stainless steel
<b>Design</b>	Miniature	Compact			Medium duty		General purpose			EN50041	EN50047 metal housing	EN50047 plastic housing	EN50047 compatible	Heavy duty		
<b>Typical Applications</b>	Commercial, light industrial	Industrial, transportation machinery; low cost to replace	Industrial, transportation machinery		Commercial, industrial, transportation machinery		Industrial, transportation machinery		Commercial, industrial	Commercial, industrial, transportation machinery			Heavy-duty industrial and transportation, Higher cost to replace			
<b>Certifications</b>	CCC, CE, cULus	CE, CCC, cULus	CE	CE, cURus	CE, CSA, UL	CE	US: select listings CSA & UL; EU: CE	US: no certifications; EU: CE	CE, CSA, UL	CE, CCC, CSA, UL; IEC/EN 60947-5-1	CE, CCC, CSA, UL; IEC/EN 60947-5-1	CE, CCC, CSA, UL; IEC/EN 60947-5-1	CE, CCC, CSA, UL; IEC/EN 60947-5-1	CE, CCC, CSA, UL	CE, CSA, UL	CE, CCC, CSA, UL
<b>Mounting, centers or bushing diameter (mm)</b>	21 x 56	20 or Ø 12 bushing	25,4 or Ø 14 bushing	25,4 or Ø 14 bushing	Side: 25,4; Flange: 41,3	Side: 68,3 x 25,4 or 76,0; Flange: 41,3	30 x 60	Requires 18PA style receptacle for mounting	30 x 59	30 x 60	20 to 22	20 to 22	20 to 22 and 40 to 42	30 x 60	30 x 60	30 x 60
<b>Body dimensions (L x w [depth] x h (mm))</b>	28 x 25 x 78 (including cable gland)	30,2 x 16,7 x 55,8	40 x 16 x 44	40 x 16 x 44	Side: 77,2 x 25,4 x 44,4; Flange: 77,2 x 44,4 x 54,1	Side: 76,4 x 25,4 or 45,2; Flange: 76,4 x 41,3 x 45,2	40 x 40 x 70	48,8 x 64,1 (with receptacle) x 91,2	40 x 41,5 x 68,7	42 x 42 x 82	30,5 x 31,1 x 68,0	30,5 x 32,6 x 66,5	65,0 x 31,1 x 68,3	One pole: 41,2 x 44,5 x 74,9 Two pole: 47,8 x 45,5 x 89,7	One pole: 41,2 x 44,5 x 74,9 Two pole: 47,8 x 45,5 x 89,8	47,8 x 45,5 x 93,7
<b>Environmental Sealing</b>	IP67	IP67, NEMA 1,4, 12, 13	IP 66, 67, 68	IP 66, 67, 68; NEMA 1, 2, 3, 3R, 4, 6, 6P, 12 (boot seal), 13	N Series: IP66, NEMA 1, 3, 4; Q Series: IP40, NEMA 1	N Series: IP65; Q Series: IP50	US: NEMA 1, 3, 4, 6 and 13; EU: IP67, NEMA 1, 4 and 13	US: NEMA 1, 3, 4, 6 and 13; EU: IP67, NEMA 1, 4 and 13	IP67	IP67, NEMA 1, 4, 12, 13	IP66, NEMA 1, 4, 12, 13	IP66/67, NEMA 1, 4X (indoor use only), 12, 13	IP66, NEMA 1, 4, 12, 13	IP65, 66, 67; NEMA 1, 3, 4, 4X, 6, 6P, 12, 13	NEMA 1, 6, 6P, 12, 13	NEMA 1, 3, 3R, 4, 4X, 6, 6P, 13
<b>Operating Temperature</b>	-20 °C to 70 °C	-25 °C to 75 °C	0 °C to 70 °C; optional -40 °C to 70 °C		-32 °C to 71 °C; optional -40 °C to 71 °C	-30 °C to 70 °C	-30 °C to 70 °C; optional -30 °C to 120 °C	-30 °C to 70 °C	-10 °C to 80 °C	-25 °C to 85 °C; side rotary: -40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-40 °C to 85 °C	-12 °C to 121 °C; optional -40 °C to 121 °C		
<b>Electrical</b>	AC-15 A300; DC-13 Q300 10 A thermal	AC15, A300; DC13, Q300: one pole 10 A Thermal; two pole 5 A Thermal	AC14, D300; DC13, R300: 5 A, 250 Vac	AC14, D300; DC13, R300: 5 A, 250 Vac	One pole: AC15, B300; 5 A Thermal; 15 A, 480 Vac	AC15, A300; DC13, Q300; 10 A Thermal	US: 10 A, 480 Vac; EU: AC15, A300; DC13, P300	US Style, 10 A, 480 Vac; EU: AC15, A300; DC13, P300	10 A, 300 Vac; 6 A 24 Vdc	AC15, A600; DC13, Q300: 10 A Thermal	AC15, A300; DC13, Q300: 10 A Thermal	AC15, A300; DC13, Q300: 10 A Thermal	AC15, A300; DC13, Q300: 10 A Thermal	AC15, A600; DC13, R300: 10 A Thermal	AC15, A600; DC13, R300: 10 A Thermal	AC15, A600; DC13, R300: 10 A Thermal
<b>Positive opening NC contacts</b>	Side rotary only	Yes	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes	No	No	No
<b>Electrical connection*</b>	Cable gland	Pre-cabled or M12 connector	Pre-cabled or M12 connector	Pre-cabled or M12 connector	Threaded conduit, pre-cabled, or mini-style connector	Threaded conduit	Threaded conduit	Threaded conduit	Threaded conduit	Threaded conduit, pre-cabled, or connector	Threaded conduit, pre-cabled, or connector	Threaded conduit, pre-cabled, or connector	Threaded conduit, pre-cabled, or connector	Threaded conduit, pre-cabled, or connector	Threaded conduit, pre-cabled, or connector	Threaded conduit, pre-cabled, or connector

\* Switches with cable gland or threaded conduit have terminal screws for electrical connection.

**Find out more**

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office. To learn more about Honeywell's sensing and switching products, call +1-815-235-6847 or 1-800-537-6945, visit [sensing.honeywell.com](http://sensing.honeywell.com), or e-mail inquiries to [info.sc@honeywell.com](mailto:info.sc@honeywell.com)

**Honeywell Sensing and Internet of Things**

9680 Old Bailes Road  
Fort Mill, SC 29707  
800-582-4263  
[www.honeywell.com](http://www.honeywell.com)

002406-4-EN | 4 | 03/19  
© 2019 Honeywell International Inc. All rights reserved.



# SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS

Est.1899

At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

# [www.scatts.co.uk](http://www.scatts.co.uk)