

PS61 – OEM Subminiature Pressure Switch

- ▶ 10 to 4,350 psi (0.7 to 300 bar)
- ▶ Exceptional Size-to-Pressure-Range Ratio
- ▶ Perfect for Demanding Applications

Available with enhanced ingress protection and integral electrical connections. These subminiature pressure switches are suitable for a wide range of hydraulic and pneumatic applications including medical, general industrial, fire suppression, and off highway vehicle.

Specifications

Switch*	100 VA Max.
Repeatability	See Table 2
Deadband	See Table 2
Wetted Parts (Pressure Range Codes 10-60)	
Diaphragm	Low-Temp Nitrile (optional FKM, FVMQ [Fluorosilicone] or EPDM)
Fitting	Zinc-Plated Steel (316 L Stainless Steel available)
Wetted Parts (Pressure Range Codes 70-100)	
Seal	Internally Lubricated Nitrile (optional FKM or EPDM)
Piston	Hardened alloy steel
Bearing	Proprietary plastic resistant to almost all chemicals
Fitting	Zinc-Plated Steel
Temperatures	
Fluid	See Table 1
Ambient	-40°F to +250°F (-40°C to +121°C)
Storage	-65°F to +275°F (-54°C to +135°C)
Vibration	
Sinusoidal	MIL-STD-202G, Method 204D, 173m ² /sec, 91-2000Hz, 8 hours/axis
Random	MIL-STD-202G, Method 214A, 146m ² /sec, 5-2000 Hz, 8 hours/axis
Shock, Operating	MIL-STD-202G, Method 213B, 500m ² /sec, 18X
Salt Spray	ASTM B117, 95°F (35°C) for 96 hours
Thermal Shock	-40°F to +250°F (-40°C to +121°C), 1 hour dwells, 1 minute change, 15 cycles
Life Cycle**	2 MM cycles with checks every 250k for all 10 pressure ranges. Range 10-40: 0 - 500 - 0 PSI @ ~1Hz Range 40-60: 0 - 3000 - 0 PSI @ ~1Hz Range 70-100: 0 - 6000 - 0 PSI @ ~1Hz
Approvals	CE, RoHS

* Gold contacts (option G) may be required for less than 12 VDC and 20 mA.

** Contact Factory for life cycle on FVMQ (Fluorosilicone) diaphragm option.

Electrical Connectors








1/4" Spade	6-32 Terminal Screws	Amp Superseal 1.5	Deutsch DT04-2P	Flying Leads	Flying Leads with Shrink Tubing	Cable
						
Ingress Protection	IP00					
	IPX7 Per IEC 60529 (1 Meter Submergence) IPX9K Per DIN40050-9 (High Pressure/High Temperature Washdown) IP6KX Per DIN40050-9 (Inorganic Dust Intrusion)					



Table 1 – Recommended Fluid Temperature Limits

Seal Material	Range
Nitrile (Pressure Range Codes 10-60)	-22°F to +250°F (-30°C to +121°C)
FVMQ (Pressure Range Codes 10-40)	-40°F to +250°F (-40°C to +121°C)
Nitrile (Pressure Range Codes 70-100)	15°F to 250°F (-9°C to +121°C)
FKM (All Ranges)	0°F to 250°F (-18°C to +121°C)
EPDM (All Ranges)	-10°F to +250°F (-23°C to +121°C)

Notes:

- Switches may function below the cold temperature limit but the set points and deadband will increase. Consult factory for details.
- Temperature performance is dependent on set point and fluid viscosity (fluids must remain free flowing liquids for Ranges 70-100).
- Ranges 70-100 not recommended for use with gases.

How To Order

Use the **Bold** characters from the chart below to construct a product code. Please reference Notes.

PS61 **-10** **-4MNZ** **-A** **-SP** **-X-X-XX**

1
2
3
4
5

① Pressure Range Code

Insert Pressure Range Code from Table 2, below.

② Pressure Fitting¹

12L14 Zinc-Plated Steel

-2MNZ=1/8" NPT Male

-4MNZ=1/4" NPT Male

-2MGZ=1/8-28 BSPP; ISO 228-G 1/8 B

(Pressure Range Codes 10-60 Only)

-4MGZ=1/4-19 BSPP; ISO 228-G 1/4 B

-4MSZ=7/16"-20 SAE J1926-2

-6MSZ=9/16"-18 SAE J1926-2

-M10Z=M10 x 1.0 ISO 6149-2

-M12Z=M12 x 1.5 ISO 6149-2

-M14Z=M14 x 1.5 ISO 6149-2

316 Stainless Steel (Range 10-60 Only²)

-2MNS=1/8" NPT Male

-4MNS=1/4" NPT Male

-4MGS=1/4-19 BSPP; ISO 228-G 1/4 B

-4MSS=7/16"-20 SAE J1926-2

-6MSS=9/16"-18 SAE J1926-2

③ Circuit

-A=SPST/N.O.

-B=SPST/N.C.

④ Electrical Termination

-SP=2x 1/4" x 1/32" Spade, Factory Set or Adjustable³

-TS=6-32 Terminal Screws, Factory Set or Adjustable³

-SS=Amp Superseal 1.5 Integral Male, Factory Set

-DT=Deutsch DT04-2P Integral Male, Factory Set

-FLAXX=18 AWG Flying Leads⁴, Adjustable³

-FLFXX=18 AWG Flying Leads⁴, Factory Set

-FLSAXX=18 AWG Flying Leads w/PVC Shrink Tubing⁴, Adjustable³

-FLSFXX=18 AWG Flying Leads w/PVC Shrink Tubing⁴, Factory Set

-CABXX=18 AWG PVC Cable⁵, Factory Set

⑤ Options

-V=FKM

-E=EPDM

-F=FVMQ (Fluorosilicone; Pressure Range Codes 10-40 Only)⁶

-G=Gold Contacts

-OF=Oil Free Cleaned (Pressure Range Codes 10-60 Only; Stainless Steel Housing Required)

-RB=Rubber Boot (Shipped Loose)

-WF=Weather Pack Connector, Female P/N 12015792

-WM=Weather Pack Connector, Male P/N 12010973

-DE=Deutsch Connector, Male P/N DT04-2P-E003

-FS=Factory Set Specify Value & Rising/Falling

Notes:

1. Other fittings and materials available. Consult factory.
2. Consult factory for use with Pressure Range 70-100.
3. Use a Security hex key, 5/32" or 4mm, to adjust set point. (Tamper-resistant hex bit available as Gems P/N 249230)
4. 18" is standard. Specify lead length in inches (max. 48"). e.g. -FLA18 or -FLF30.
5. 36" is minimum. Specify cable length in inches. e.g. -CAB36 or -CAB120.
6. Consult factory for life cycle information.

Table 2 – Pressure Range Codes

Pressure Range Code	Style	Recommended Media	Pressure Range	Repeatability*	Average Deadband**	Proof Pressure	Burst Pressure
10	Diaphragm	Liquids & Gases	10-60 psig (.7-4.1 bar)	±1.5 psi (0.10 Bar) +3% of setting	12% of setting	6,000 psi (414 bar)	9,000 psi (620 bar)
20			40-150 psig (2.8-10.3 bar)	±2.5 psi (0.17 Bar) +3% of setting	13% of setting		
30			75-275 psig (5.2-19 bar)	±3.75 psi (0.26 Bar) +3% of setting	13% of setting		
40			150-500 psig (10.3-34.5 bar)	±5 psi (0.34 Bar) +3% of setting	14% of setting		
50			275-800 psig (19-55.1 bar)	±8 psi (0.55 Bar) +3% of setting	15% of setting		
60	Piston	Liquids	400-1,350 psig (27.6-93 bar)	±13 psi (0.90 Bar) +3% of setting	17% of setting	7,000 psi (483 bar)	22,000 psi (1517 bar)
70			510-1,235 psig (35-85 bar)	±30 psi (2.1 Bar) +4% of setting	14% of setting		
80			800-1,960 psig (55-135 bar)	±48 psi (3.3 Bar) +4% of setting	17% of setting		
90			1,835-3,115 psig (125-215 bar)	±110 psi (7.6 Bar) +6% of setting	21% of setting		
100			2,970-4,350 psig (205-300 bar)	±190 psi (13.1 Bar) +6% of setting	24% of setting		

* Repeatability and set point of units will vary depending on temperature, fluid viscosity, cycle rate and ramp rate. Repeatability values are based on room temperature. Long term inactuation will lead to a higher initial set point reading due to the non-linear behavior of the elastomer diaphragms or seals. Fluids with low and stable viscosities over the expected temperature range will exhibit better performance.

** Deadband values are an approximation at room temperature with nitrogen or compressed air (Ranges 10-40) or a 100 Cp fluid (Ranges 40-100). At lower temperatures and/or higher fluid viscosities the deadband will be much larger than the value shown. At high fluid temperature and a rapid cycle rate, the deadband may be lower than the approximations given. Please consult the factory if specific statistical analysis is required.



SCATTERGOOD & JOHNSON LTD

ELECTRICAL ENGINEERING & FLUID CONTROL DISTRIBUTORS


At Scattergood & Johnson Ltd, we pride ourselves on being a technical distributor to specialist industries.

Working with a range of quality product suppliers across a number of specialist markets, we are not your average 'box shifter' - we are your technical and supply chain partner.

We fully support every product we sell - for free! Our internal team and external sales engineers can answer any product or application question, no matter the complexity.

Backing up this technical ability is a range of 50,000+ products available from stock for nationwide next day delivery (same day if required!), or you can collect what you need from any of our trade counters around the UK.

Select your specialist interest below to learn more about how we can help.



Online, In Branch and On the Road - Scattergood & Johnson Ltd, there when you need us.

www.scatts.co.uk